



Product Specifications

Construction	Textured Loop
Backing	PremierBac® Plus (A)
Dye Method	Beck Dyed
Fiber Type	Type 6,6 Nylon
Face Weight	28 oz./sy (949 grams/m2)
Pile Density	8490 oz./y3 (314.81 kg/m3)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Stitches Per Inch	12 stitches/in (4.72 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	PremierBac Plus Encore® RE & Type 6,6 Nylon Fiber
Optional Warranties	Endure Plus TitanBac Plus


Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Indoor Air Quality	GLP3678
Total Recycled Content	23.16%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways



3061 Coincide



3062 Medley



3063 Synthesize




3064 Consolidate



3067 Meld



3068 Combine




3069 Incorporate



3070 Compose



3071 Blend



3072 Unify