



**Installation Methods:** Parquet, Herringbone, Basketweave, Ashlar

Product Specifications

|                     |                                                                                                                                                                                                                   |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Construction        | Textured Patterned Loop                                                                                                                                                                                           |
| Backing             | Nexus® Modular                                                                                                                                                                                                    |
| Dye Method          | Solution/Yarn Dyed                                                                                                                                                                                                |
| Fiber Type          | Encore® BCF (with recycled content)                                                                                                                                                                               |
| Face Weight         | 22 oz./sy (746 grams/m2)                                                                                                                                                                                          |
| Pile Density        | 6881 oz./y3 (255.15 kg/m3)                                                                                                                                                                                        |
| Pattern Repeat      | N/A                                                                                                                                                                                                               |
| Gauge               | 1/12 (4.72 rows/cm)                                                                                                                                                                                               |
| Stitches Per Inch   | 12.6 stitches/in (4.96 stitches/cm)                                                                                                                                                                               |
| Standard Size       | 12" x 48" approx. (30.48cm x 121.92cm)                                                                                                                                                                            |
| Standard Adhesive   | Commercialon Premium Modular Adhesive                                                                                                                                                                             |
| Optional Adhesive   | TileTabs                                                                                                                                                                                                          |
| Standard Warranties | <b>Nexus Modular</b><br><b>Commercialon Adhesive for Modular Carpet &amp; LVT</b><br><b>Encore® BCF (with ColorLoc Plus)</b>                                                                                      |
| Optional Warranties | <b>Nexus Cushion Modular</b><br><b>Tile Tabs</b><br><b>Nexus Cushion Adhesive</b><br><b>Commercialon High Moisture Adhesive for Modular Carpet and LVT</b><br><b>Nexus FC Cushion</b><br><b>Encore® 100 Fiber</b> |

Special Technologies

|                        |          |
|------------------------|----------|
| Colorloc® Plus         | Standard |
| ProSept® Antimicrobial | Optional |
| ProTex® Soil Release   | Standard |
| Sentir® Odor-Blocker   | Optional |

Environmental Specifications & Tests

|                        |                                    |
|------------------------|------------------------------------|
| NSF 140:               | Gold Certified                     |
| Indoor Air Quality     | GLP9716                            |
| Total Recycled Content | 45.95%                             |
| Radiant Panel          | Class 1                            |
| Smoke Density          | Less than 450 flaming (ASTM E 662) |
| Static Test            | Less than 3 kv (AATCC-134)         |
| ADA Compliance         | Compliant For Accessible Routes    |
| Pill Test              | Yes                                |
| Lightfastness          | Yes                                |

Colorways



2085 Lotus



2086 Bliss



2087 Calm



2088 Harmonic



2089 Tranquil



2090 Remedy



2091 Serene



2092 Clear



2093 Stillwater




2094 Breeze



2095 Escape



2096 Solace



2097 Shadow

[www.jjflooringgroup.com](http://www.jjflooringgroup.com)