

# FIBERGLASS PANELS



USG Chambray™ 208

TO ORDER SAMPLES, GO TO [USG.COM](http://USG.COM)

USG Chambray™

USG Tabaret™

USG Tabaret™ Perforated

## FEATURES AND BENEFITS

- Lightweight and good NRC (sound absorption).
- Moisture-resistant vinyl face allows easy cleaning and use in high-humidity areas.
- Ideal for open spaces like retail and grocery stores.

## SUBSTRATE

- Fiberglass

## PRODUCT SPECIFICATIONS

| Pattern                           | Item No.   | Edge   | Panel Size | Pcs./<br>Carton | Sq. Ft./<br>Carton | Ctns./<br>Pallet | Fire<br>Rating | Sound Control |     | Technical Information |         |     |                                     | Recycled<br>Content | USG<br>Commercial<br>Equivalent  |
|-----------------------------------|------------|--------|------------|-----------------|--------------------|------------------|----------------|---------------|-----|-----------------------|---------|-----|-------------------------------------|---------------------|----------------------------------|
|                                   |            |        |            |                 |                    |                  |                | NRC           | CAC | LR                    | R-Value | VOC | Mold,<br>Mildew & Sag<br>Resistance |                     |                                  |
| <b>USG CHAMBRAY™</b>              | <b>208</b> | SQ<br> | 2'x4'x5/8" | 12              | 96                 | 12               | Class A        | 0.50          | 20  | 0.76                  | 2.7     | —   |                                     | 64%                 | USG Premier Hi-Lite™ Twill 7053G |
| <b>USG TABARET™</b>               | <b>209</b> | SQ<br> | 2'x4'x5/8" | 12              | 96                 | 12               | Class A        | 0.50          | 20  | 0.76                  | 2.7     | —   |                                     | 64%                 | USG Premier Hi-Lite™ Kapok 7057G |
| <b>USG TABARET™</b><br>Perforated | <b>210</b> | SQ<br> | 2'x4'x5/8" | 12              | 96                 | 12               | Class A        | 0.70          | 20  | 0.76                  | 2.7     | —   |                                     | 64%                 | USG Premier Hi-Lite™ Kapok 7055G |

### ClimaPlus™ Warranty Performance

Fiberglass substrate is inherently resistant to the growth of mold and mildew. Includes sag-resistance performance.

### High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

### FOOTNOTES

#### **ASTM E84 surface-burning characteristics**

Class A  
Flame Spread: 25 or less  
Smoke Developed: 50 or less

#### **Maintenance**

Can be cleaned easily with a damp sponge.