



Painted Hills (PHL)

Product Quick Specs

Style Name/Number	Painted Hills PHL
Color Name/Number	Clay PHL14
Construction	Textured Loop
Standard Backing	PremierBac® Plus
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	18 oz./sy (610 grams/m2)
Pile Density	9290 oz./y3 (344.48 kg/m3)
Pattern Repeat	.40" (w) x .75" (l) approx. (1.02cm x 1.91cm)
Gauge	1/10 (3.94 rows/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Smoke Density	Less then 450 flaming
Static Test	Less then 3 kv
Standard Warranties	Commercialon Premium Broadloom Adhesive PremierBac Plus Encore SD Ultima Fiber
Optional Warranties	Endure Plus TitanBac Plus Encore® 100 Fiber



Products Installed



Painted Hills PHL
PHL14 Clay

CARPET

Installation Method

Custom

This three dimensional rendering is for visualization purposes only and may not be an exact representations of the selected products. Pile heights may vary from product to product and adhesive requirements may vary depending on product selection. The review of actual product samples are recommended before final selection. Please contact your EF Contract sales representative with any questions. This unique carpet design is protected under the U.S. Copyright Act of 1976. Any unauthorized copying or duplication of this design constitutes copyright infringement in violation of federal law.