

GENERAL INFORMATION:

Code:	T202
Material:	Stainless steel
Operating Temperature:	-22°F~122°F
IP Rating:	IP 65
Voltage:	110-277V
Source Type:	LED
CRI:	90
Dimming:	0-10V

DIMENSIONS:

Height (AA):	24" / 36" / 45" / 48" / 56" / 62" / 80" / 120" / 144" / CUS*
Lens size (BB):	2" / 4" / 5" / 6" / 8" / 12" / 16" / 18" / 24" / 36" / 48" / CUS*
Diameter(CC):	5" / 6" / 8" / 10" / 12" (depends on a security rating needed*)


LENS TYPE (DD):

20	Standard Clear Lens
21	Frosted acrylic lens

FINISH (EE):

11	316 Stainless steel with a #4 swirl brushed stainless surface finish
12	Custom RAL

Stainless powder coated standard colors:

				
392 White	393 Green	394 Corten	395 Grey	396 Black

SECURITY RATING (FF):

BDS-C40FB36-ST	ASTM C40 CRASH RATED FIXED BOLLARD
BDS-M30-FB-ST	ASTM M30 CRASH RATED FIXED BOLLARD
BDS-M30FB-SH	ASTM M30 CRASHED RATED SHALLOW BOLLARD
BDS-M50FB-SH	ASTM M50 CRASHED RATED SHALLOW BOLLARD
BDS-PU40FB36-ST	ASTM PU40 CRASH RATED FIXED BOLLARD



**BULLARD
BOLLARDS**

**TOTEM 2 SECURITY RATED OR STANDARD LIT BOLLARD AND
COLUMN**

CODE: T202-AA-BB-CC-DD-EE-FF-MM-QQ-JJ-OO-RR



COLOUR TEMPERATURE (MM):

31	3000K
32	4000K
33.	5000K
34.	RGB

LIGHT DISTRIBUTION (QQ):

Type A:	180°
Type B:	360°

LIGHT SOURCE OUTPUT BOLLARD (JJ):


40	15 W / 396 lm
41	20 W / 580 lm
42	25 W / 590 lm
43	25 W / 880 lm
44	30 W / 1200 lm

LIGHT SOURCE OUTPUT COLUMN (OO):


50	20 W / 970 lm
51	30 W / 1200 lm
52	35 W / 1400 lm
53	40 W / 1780 lm
54	45 W / 2600 lm
55	55 W / 3200 lm
56	65 W / 3810 lm

LENS COVER ON REQUEST (RR):


Code: BB




Code: ZG




Code: RB




Code: MM




Code: LD



Code: GR



Code: BS



sales@gordonbullard.com

www.bullardbollards.com

1-877-964-4646



991 South Gull Lake Dr

Richland, MI 49083

USA