



GH1143.AHFT300EN
1143.AHF.T

GH1143.AHFT400EN
1143.ALF.T

H(m)	φ(m)	Lux Medi
5	3.7	17
4	3.0	26
3	2.2	47
2	1.5	106
1	0.7	423

H(m)	φ(m)	Lux Medi
5	3.7	18
4	3.0	28
3	2.2	51
2	1.5	114
1	0.7	455

ELECTRICAL and LIGHTING SOURCE for MODEL: GH1143.AHFT300EN 1143.AHF.T

Description:	1 x 6 W LED 3000 K CRI>85 540 lm
Operating Power:	110-277V / 50-60 Hz
Number of heads:	1
Number of circuits:	1
Driver positioning:	Integral
Control gear type:	Electronic
Cable entry:	Fixture supplied with pre-wired cable H05RN-F
Emergency kit:	Not available
Light source:	LED
Power:	6 W
ZVEI - Led Type:	DOB
Color temperature:	3000 K
Color rendering index:	CRI>85
Nominal LED emission:	540 lm
Light source:	Included
Ambient temperature operating range:	- 20 °C ÷ +35 °C

ELECTRICAL and LIGHTING SOURCE for MODEL: GH1143.AHFT400EN 1143.ALF.T

Description:	1 x 6 W LED 4000 K CRI>85 580 lm
Operating Power:	110-277V / 50-60 Hz
Number of heads:	1
Number of circuits:	1
Driver positioning:	Integral
Control gear type:	Electronic
Cable entry:	Fixture supplied with pre-wired cable H05RN-F
Emergency kit:	Not available
Light source:	LED
Power:	6 W
ZVEI - Led Type:	DOB
Color temperature:	4000 K
Color rendering index:	CRI>85
Nominal LED emission:	580 lm
Light source:	Included
Ambient temperature operating range:	- 20 °C ÷ +35 °C

OPTICAL:

Beam Type:	Wall-Effect 1 [21°-40°] medium
Beam angle:	33°
Light distribution:	Direct lighting
Beam directionability:	Fixed
Diffuser material:	Soda-lime tempered glass 5mm
Diffuser finish:	Clear
Reflector material:	PMMA lens

FINISH CODE:

■ .05 Dark grey (matt)

■ .19 Light Grey