



GH1143.LVFT300EC
1143.CAF.T

GH1143.LVFT400EC
1143.CBF.T

H(m)	φ(m)	Lux Medi
5	3.7	37
4	3.0	57
3	2.2	102
2	1.5	230
1	0.7	919

H(m)	φ(m)	Lux Medi
5	3.7	38
4	3.0	60
3	2.2	106
2	1.5	239
1	0.7	955

ELECTRICAL and LIGHTING SOURCE for MODEL: GH1143.LVFT300EC 1143.CAF.T

Description:	1 x 9 W LED 3000 K CRI>90 1173 lm
Operating Power:	500 mA
Number of heads:	1
Number of circuits:	1
Control gear:	500 mA not included
Driver positioning:	Remote
Control gear type:	Electronic
Cable entry:	Fixture supplied with pre-wired cable H05RN-F
Emergency kit:	Not available
Light source:	LED
Power:	9 W
LED voltage range:	18V
Current:	500 mA
ZVEI - Led Type:	COB
Color temperature:	3000 K
Binning:	Step MacAdam 3
Color rendering index:	CRI>90
Nominal LED emission:	1173 lm
Light source:	Included
Ambient temperature operating range:	- 20 °C ÷ +35 °C

ELECTRICAL and LIGHTING SOURCE for MODEL: GH1143.LVFT400EC 1143.CBF.T

Description:	1 x 9 W LED 4000 K CRI>90 1218 lm
Operating Power:	500 mA
Number of heads:	1
Number of circuits:	1
Control gear:	500 mA not included
Driver positioning:	Remote
Control gear type:	Electronic
Cable entry:	Fixture supplied with pre-wired cable H05RN-F
Emergency kit:	Not available
Light source:	LED
Power:	9 W
LED voltage range:	18V
ZVEI - Led Type:	COB
Color temperature:	4000 K
Binning:	Step MacAdam 3
Color rendering index:	CRI>90
Nominal LED emission:	1218 lm
Light source:	Included
Ambient temperature operating range:	- 20 °C ÷ +35 °C

OPTICAL:

Beam Type:	Wall-Effect 1 [21°-40°] medium
Beam angle:	36°
Light distribution:	Direct lighting
Beam directionability:	Fixed
Diffuser material:	Soda-lime tempered glass 5mm
Diffuser finish:	Clear
Reflector material:	PMMA lens

FINISH CODE:

.05 Dark grey (matt)

.19 Light Grey

ACCESSORIES:



Driver 22W
500mA IP20
AC206-500mA



Driver 20W
500mA IP67
AC689-500mA-
IP67