





LED VERSIONS:

H(m)	φ(m)	Lux Medi
5	22.9	1
4	18.3	2
3	13.7	3
2	9.2	7
1	4.6	30

E26:

H(m)	φ(m)	Lux Medi
5	32.2	0
4	25.7	1
3	19.3	1
2	12.9	2
1	6.4	10

CONSTRUCTIVE & DIMENSIONAL:

Application field:	Porch, balconies & terraces, Passageways, Pathios, Covered entrances & walkways, Walkways and driveways
Construction material:	Die-cast aluminum EN AB 44100 highly resistant to oxidation
External screws:	Stainless steel A4-70 treated with highly antioxidant water-repellent lubricating solution
Diameter:	270mm(10,62")

ELECTRICAL and LIGHTING SOURCE for MODEL: GH0994.BRXO300EN 0994.147.O

Description:	1 x 13 W LED 3000 K CRI>85 2040 lm
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	1
Driver positioning:	Integral
Control gear type:	Electronic
Emergency kit:	Not available
Light source:	LED
Power:	13W
ZVEI - Led Type:	DOB
Color temperature:	3000 K
Color rendering index:	CRI>85
Nominal LED emission:	2040 lm
Light source:	Included
Ambient temperature operating range:	-20 °C ÷ +35 °C

ELECTRICAL and LIGHTING SOURCE for MODEL: GH0994.BRXO400EN 0994.148.O

Description:	1 x 13 W LED 4000 K CRI>85 2140 lm
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	1
Driver positioning:	Integral
Control gear type:	Electronic
Emergency kit:	Not available
Light source:	LED
Power:	13W
ZVEI - Led Type:	DOB
Color temperature:	4000 K
Color rendering index:	CRI>85
Nominal LED emission:	2140 lm
Light source:	Included
Ambient temperature operating range:	-20 °C ÷ +35 °C

ELECTRICAL and LIGHTING SOURCE for MODEL: GH0994.36X0XXEX 0994.36F.O

Description:	1 x 57 W
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	1
Emergency kit:	Not available
Lampholder:	E26
Power:	57W
ZVEI - Led Type:	INC
Light source:	Not Included
Ambient temperature operating range:	-20 °C ÷ +35 °C

OPTICAL:

Beam Type:	Wall extrawide
Light distribution:	Symmetric
Beam directionability:	Fixed
Diffuser material:	Vandal proof polycarbonate UV resistant
Diffuser finish:	Opal

FINISH CODE:

.05 Dark grey (matt)	.19 Light Grey	.01 White (matt)
.02 Black (matt)	.45 Corten	.80 Sand