



Sarita #2833

Product Specification

Face Construction	Imperial			Metric	
Construction	Element-Enhanced Loop				
Tufted Pile Weight	28	oz/sq yd		949	g/sq m
Gauge	1/10	inch		39.4	rows/10 cm
Stitches per Inch	10	stitches / inch		39.4	stitches/10 cm
Pile Height	0.250	inch	High	6.4	mm
	0.187	inch	Medium	4.7	mm
	0.062	inch	Low	1.6	mm
Total Weight	64.0	oz/sq yd		2170	g/sq m
Fiber System	100% C.F. Lextron Enviro-Green Solution Dyed Nylon				
Dye Method	Solution Dyed				
Pattern Repeat	0.6" W x 0.78" L			15 mm W x 20 mm L	
Primary Backing	Woven Polypropylene				
Backing Construction	Super-Lok® enriched latex backing				
Width	12	feet		366	cm

Product Testing/Information

Surface Flammability	Flooring Radiant Panel	ASTM E-648 Class 1
	Smoke Density	ASTM E-662 Less than 450

The product, represented by averages of testing from random samplings of production lots, meets or exceeds the above Test Results.
Enviro-Green yarn has 10% pre-consumer recycled content.
Recommended for moderate (rooms) carpet traffic levels.

Installation and Maintenance

Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104. Carpet must be over manufacturer's recommended pad.
Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction. IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns.
Due to the manufacturing process of a tip shear product, the finished yarn weight will vary more than normal manufacturing tolerances and side match cannot be guaranteed.

Warranties

Limited 10 Year Abrasive Wear Warranty
Limited 10 Year Manufacturing Warranty

Product Notes

1. All specifications are subject to normal manufacturing tolerances.
2. Dye lots may vary from samples.
3. The use of chair pads under roller caster chairs is required in order to maintain full limited warranty coverage.
4. Tarkett reserves the right to change specifications and construction materials without notice due to raw material shortages or technological improvements, contact your representative for confirmation.

Tarkett North America

Technical Services Department
285 Kraft Drive
Dalton, GA 30721
USA: 800-871-3211

www.tarkettna.com

© 2022 Tarkett USA Inc. 10/2022