

Sarita #2833

Product Specification

Face Construction	Imperial		Metric	Metric		
Construction	Element-Enhanced Loop					
Tufted Pile Weight	28	oz/sq yd		949	g/sq m	
Gauge	1/10	inch		39.4	rows/10 cm	
Stitches per Inch	10	stitches / ir	nch	39.4	stitches/10 cm	
Pile Height	0.250	inch H	ligh	6.4	mm	
	0.187	inch M	1edium	4.7	mm	
	0.062	inch L	ow	1.6	mm	
Total Weight	64.0	oz/sq yd		2170	g/sq m	
Fiber System	100% C.F. Lextron Enviro-Green Solution Dyed Nylon					
Dye Method	Solution Dyed					
Pattern Repeat	0.6" W x 0.78" L 15 mm			15 mm	W x 20 mm L	
Primary Backing	Woven Polypropylene					
Backing Construction	LifeLONG® acrylic polymeric backing					
Width	12	feet	•	366	cm	
Product Recycled Content	38.4%	overall post-industrial recycled content				

Product Testing/Information

Surface Flammability	Flooring Radiant Panel	ASTM E-648 Class 1
	Smoke Density	ASTM E-662 Less than 450

The product, represented by averages of testing from random samplings of production lots, meets or exceeds the above Test Results. Enviro-Green yarn has 10% pre-consumer recycled content.

Recommended for moderate (rooms) carpet traffic levels.

Installation and Maintenance

Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104. Carpet must be over manufacturer's recommended pad.

Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction. IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns. Due to the manufacturing process of a tip shear product, the finished yarn weight will vary more than normal manufacturing tolerances and side match cannot be guaranteed.

Warranties

Limited 10 Year Abrasive Wear Warranty Limited 10 Year Manufacturing Warranty

Product Notes

- 1. All specifications are subject to normal manufacturing tolerances.
- 2. Dyelots may vary from samples.
- 3. The use of chair pads under roller caster chairs is required in order to maintain full limited warranty coverage.
- 4. Tarkett reserves the right to change specifications and construction materials without notice due to raw material shortages or technological improvements, contact your representative for confirmation.

Tarkett North America

Technical Services Department 285 Kraft Drive Dalton, GA 30721 USA: 800-871-3211 www.tarkettna.com

© 2022 Tarkett USA Inc. 10/2022