



## Persona #11118

## Product Specification

| Face Construction             | Imperial                                               |             | Metric |             |
|-------------------------------|--------------------------------------------------------|-------------|--------|-------------|
| Construction                  | Stratatec® Patterned Loop                              |             |        |             |
| Face Weight                   | 20                                                     | oz/sq yd    | 678    | g/sq m      |
| Gauge                         | 5/64                                                   |             | 50.4   | rows/10 cm  |
| Stitches per Inch             | 9.6                                                    |             | 37.8   | pu/10 cm    |
| Tuft Density                  | 122.88                                                 | tufts/sq in | 19.0   | tufts/sq cm |
| Pile Height Average           | 0.187                                                  | inch        | 4.7    | mm          |
| Pile Thickness                | 0.067                                                  | inch        | 1.7    | mm          |
| Pile Density                  | 10,746                                                 | oz/cu yd    | 397.6  | kg/cu m     |
| Fiber System                  | Dynex SD® Nylon (Permanent Stain Resistance)           |             |        |             |
| Dye Method                    | Solution Dyed                                          |             |        |             |
| Fluorine-Free Soil Protection | Eco-Ensure (Cradle to Cradle™ v3.1 Certified Platinum) |             |        |             |
| Primary Tufting Substrate     | Synthetic Non-Woven                                    |             |        |             |
| Pattern Match                 | Not required                                           |             |        |             |

### Third Party Environmental Certifications

| Product                                  | Recycled Content |              | Green Label    | NSF 140       | Cradle to Cradle                                                                    |
|------------------------------------------|------------------|--------------|----------------|---------------|-------------------------------------------------------------------------------------|
|                                          | Overall          | Postconsumer | Plus Certified | SCS Certified | Certified™ v3.1                                                                     |
| ethos® Modular with Omnicoat Technology® | 56 - 79%         | 30%          | GLP8320        | Gold          | Silver                                                                              |
| Flex-Aire Modular® Cushion               | 28 - 46%         | 22%          | GLP6558        | Gold          |                                                                                     |
|                                          |                  |              |                |               |  |
|                                          |                  |              |                |               | SILVER                                                                              |

### Product Testing/Information

|                          |                                                                                |
|--------------------------|--------------------------------------------------------------------------------|
| Antimicrobial Chemicals  | No antimicrobials (EPA Registered pesticides) added to product (ASTM E2471-05) |
| Electrostatic Propensity | ≤3.0 kV (AATCC 134); Permanent Conductive Fiber                                |
| Surface Flammability     | Passes CPSC FF 1-70 (ASTM D-2859)                                              |
| Flooring Radiant Panel   | Class 1 (mean average CRF: 0.45 w/sq cm or higher) (ASTM E-648)                |
| Smoke Generation         | Less than 450 (ASTM E-662)                                                     |
| Colorfastness to Light   | ≥ 4 after 100 hours (AATCC 16E)                                                |
| Soil Protection          | Application Rate: 2% of Face Weight                                            |
| Stain Resistance         | > 8 (AATCC 175-08 Stain Resistance Pile Floor Coverings)                       |

### Installation Methods

|                     |                                                                  |
|---------------------|------------------------------------------------------------------|
| Wet Spread          | Backing specific Tarkett Adhesives                               |
| Installation Method | 24"x 24", Vertical Ashlar; 18"x 36" Vertical Ashlar, Herringbone |

### Product Notes

- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice. Colors may vary slightly from dye lot to dye lot.
- U.S. Patent numbers: 4,849,267; 6,406,574, US 9,988,760 B2
- Chair pads are recommended for optimum textural performance. Absent the use of chair pads, more intensive maintenance will be required for areas in direct contact with chair caster traffic, and some degree of appearance change is to be expected.

### Tarkett North America

Technical Services Department  
1104 Willowdale Road NW  
Dalton, GA 30721  
800.248.2878

[www.tarkett.com](http://www.tarkett.com)

© 2024 Tarkett USA Inc. 2/2024

[illegible]