




Urban View #04405

Product Specification

Face Construction	Imperial		Metric		
Construction	Stratatec® Patterned Loop				
Gauge	5/64		50.4	rows/10 cm	
Stitches per Inch	11.6		45.7	pu/10 cm	
Tuft Density	148.48	tufts/sq in	23.0	tufts/sq cm	
Pile Height Average	0.187	inch	4.7	mm	
Pile Thickness	0.072	inch	1.8	mm	
Pile Density	5,000	oz/cu yd	185.0	kg/cu m	Kilotex 6.7
Fiber System	Dynex SD® Nylon (Permanent Stain Resistance)				
Dye Method	100% Solution Dyed				
Fluorine-Free Soil Protection	Eco-Ensure (Cradle to Cradle™ v3.1 Certified Platinum)				
Primary Tufting Substrate	Synthetic Non-Woven				
Pattern Match	Not Required				

Third Party Environmental Certifications

Product	Recycled Content		Green Label	NSF 140	Cradle to Cradle Certified™ v3.1
	Overall	Postconsumer	Plus Certified	SCS Certified	
ethos® Modular with Omniccoat Technology®	56 - 79%	30%	GLP8320	Gold	Silver
Flex-Aire Modular® Cushion	28 - 46%	22%	GLP6558	Gold	



Product Testing/Information

Antimicrobial Chemicals	No antimicrobials (EPA Registered pesticides) added to product (ASTM E2471-05)
Electrostatic Propensity	≤3.0 kV (AATCC 134); Permanent Conductive Fiber
Surface Flammability	Passes CPSC FF 1-70 (ASTM D-2859)
Flooring Radiant Panel	Class 1 (mean average CRF: 0.45 w/sq cm or higher) (ASTM E-648)
Smoke Generation	Less than 450 (ASTM E-662)
Colorfastness to Light	≥ 4 after 100 hours (AATCC 16E)
Soil Protection	Application Rate: 2% of Face Weight
Stain Resistance	> 8 (AATCC 175-08 Stain Resistance Pile Floor Coverings)

Installation Methods

Peel and Stick	RS Adhesive System - Full Coverage Peel & Stick
Wet Spread	Backing specific Tarkett Adhesives
Installation Method	24" x 24" Vertical Ashlar

Product Notes

- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice. Colors may vary slightly from dye lot to dye lot.
- U.S. Patent numbers: 4,849,267; 6,406,574, US 9,988,760 B2
- Chair pads are recommended for optimum textural performance. Absent the use of chair pads, more intensive maintenance will be required for areas in direct contact with chair caster traffic, and some degree of appearance change is to be expected.

Tarkett North America

Technical Services Department
 1104 Willowdale Road NW
 Dalton, GA 30721
 800.248.2878

www.tarkett.com



IMPERIAL

METRIC

TEST METHOD

Warranty: Lifetime limited warranty against excessive surface wear, static, delamination, edge ravel, zippering, backing resiliency loss & stain resistance.

ethos® Modular with Omnicoat Technology®

Total Minimum Recycled Content	69.3%				
Pre-Consumer	33.3%				
Postconsumer	36.0%				
Product Size	24" x 24" Tile				
Secondary Backing	50% Recycled Content				
Intermediate Layer	Fiberglass Reinforced Sealant				
Product Construction	No Delamination per ASTM D-3936				
Secondary Backing Density	65.0	lbs/cu ft		1041	kg/cu m
Secondary Backing Thickness	0.050	inch		1.3	mm
Total Weight	87.9	oz/sq yd +/-5%		2979.5	g/sq m

Flex-Aire Modular® Cushion

Total Minimum Recycled Content	32.1%				
Pre-Consumer	6.1%				
Postconsumer	26.0%				
Product Size	24" x 24" Tile				
Secondary Backing	Fiberglass Reinforced Composite Closed Cell Cushion				
Intermediate Layer	Fiberglass Reinforced Sealant				
Product Construction	No Delamination per ASTM D-3936				
Cushion Weight	35.5	oz/sq yd		1203	g/sq m
Cushion Density	18.5	lbs/cu ft		296	kg/cu m
Cushion Thickness	0.156	inch		4.0	mm
Total Weight with RS / Non-RS	109.1	107.7	oz/sq yd +/-5%	3700	3652
Compression Set	Max. 10%				ASTM D1667
Compression Deflection	5 Min.	25 max lbs/sq inch @ 25%	352	1758	g/sq cm