
6 [159] WIDE REVEAL FRAME AND GRATE SYSTEM

TAG

Dimensional Data (inches and [mm]) are Subject to Manufacturing Tolerances and Change Without Notice



ENGINEERING SPECIFICATION: Zurn Z706

Frame and Grate System shall be 120" [3048mm] long, 6" [152mm] wide and have a 4" [102mm] clear opening. Frame shall mechanically lock into the concrete surround every 10" [254mm]. Shall be provided with standard DGC grates that lock down to frame. Zurn 6" [152mm] wide reveal Ductile Iron Slotted Grate conforming to ASTM specification A536-84, Grade 80-55-06. Ductile Iron grate is rated class C per the DIN EN1433 top load classifications. Supplied in 20" [508mm] nominal lengths with 1/2" [13mm] wide slots, and 3/4" [19mm] bearing depth. Grate has an open area of 18.57 sq. in per ft. [39,307 sq. mm per meter]. The 1/4" [6mm] thick Heavy-Duty Carbon Steel Frame Assembly conforms to ASTM specification A36 with 12 - 4" [102mm] long concrete anchors per 120" [3048mm]. Grate lockdown bars are to be integral to the frame The frame is supplied with a powder coated finish. Frames Shall be produced in the U.S.A.

PREFIX OPTIONS (Check/specify appropriate options)
___ Z Ten-foot, Heavy Duty Carbon Steel Frame with Anchor Studs*

SUFFIX OPTIONS (Check/specify appropriate options)

* Regularly furnished unless otherwise specified.

Zurn Industries, LLC | Specification Drainage Operation 1801 Pittsburgh Avenue, Erie, PA U.S.A. 16502 · Ph. 855-663-9876, Fax 814-454-7929 In Canada | Zurn Industries Limited 7900 Goreway Drive, Unit 10, Brampton, Ontario L6T 5W6 · Ph. 877-892-5216 www.zurn.com

Rev.

Date: 08/21/2020 C.N. No. 142913 Prod. | Dwg. No. Z706