## Flammability Certificate 3809 Rise Designtex

3809 Rise was tested and met the following flammability requirements:

CA TB 117-2013



Ext:

Page 1

Received: 08/25/2016 | Completed: 08/26/2016 | Letter: N1 BG | P.O.#: Test Report #: 3-15049-1-Client's Style: Rise 3809. Composition: 100% Vinyl Knit Back, Resilience Finish. Weight: 30 oz/lin yard. Product End Use:

Identification Upholstery.

Tested For: Teesha Prezeau Key Test: CA TB 117-2013 (Section 1-Cover 235

Designtex Fabric) /ACT

357 County Avenue Tel: 1-(201)-917-7738

Secaucus, NJ 07094 Fax: 1-(201)-917-7764

Test Category: Cigarette Ignition Specifier: ACT LE 2015; V 08/15 NTR 9/15

Product Category: Upholstery PC: 24H d1/SM

TEST PERFORMED: California Technical Bulletin 117-2013 - Requirements, Test Procedure and Apparatus for Testing the Smolder Resistance of Materials Used in Upholstered Furniture (June 2013 Version)

Section 1, Cover Fabric Test (Upholstery cover material is the outermost layer of fabric or related material used to enclose the main support system or upholstery materials, or both, used in the furniture item.) --

As cited by the ACT Voluntary Performance Guidelines (January 2015)

REFERENCE: ASTM E1353-08ae1

IGNITION SOURCE: SRM 1196 Cigarette

SPECIMEN TEST COMPOSITE:

Upholstery Cover Material: As described in "Client's Identification".

Standard Substrate Material: Non FR polyurethane foam, density 1.8 ± 0.05 lb/ft3

BRIEF DESCRIPTION OF TEST: Miniature cushions are prepared using the client's cover fabric over the standard filling material. The vertical or back cushions measure 8" x 8" x 2". The horizontal or seat cushions measure 8" x 5" x 2".

A lighted cigarette is placed in the crevice formed by the vertical cushion and the horizontal cushion.

The test is terminated at 45 minutes if smoldering is no longer observed.

Test measurements and observations are recorded.

-- See Page 3 for "Results" and "Conclusion" --

(Page 1 of 4)



Page 2

Received: 08/25/2016 Completed: 08/26/2016 Letter: N1 BG | P.O.#: 3-15049-1-Test Report #: Client's Style: Rise 3809. Composition: 100% Vinyl Knit Back, Resilience Finish. Weight: 30 oz/lin yard. Product End Use: Identification Upholstery. Tested For: Teesha Prezeau Key Test: CA TB 117-2013 (Section 1-Cover 235 Designtex Fabric) /ACT 357 County Avenue Tel: 1-(201)-917-7738 Ext: Secaucus, NJ 07094 Fax: 1-(201)-917-7764

PASS/FAIL/REPEAT CRITERIA: A material is considered to pass or fail based on the following criteria:

- 1. A single mock-up test specimen fails to meet the requirements of this test procedure if any of the following criteria occurs:
  - a) The mock-up test specimen continues to smolder after the 45 minute test duration;
  - b) A vertical char length (measured as specified in step 11.9 of ASTM E1353-08ae1) of more than 1.8 inches (45 mm) develops on the cover fabric.
  - c) The mock-up test specimen transitions to open flaming.
- 2. The cover fabric passes the test if three initial mock-up specimens pass the test, i.e., the cigarettes burn their entire length and the mock-ups are no longer smoldering.
- 3. If more than one initial specimen fails, the cover fabric fails the test.
- 4. If any one of the three initial specimens fails, repeat the test on additional three specimens.
- 5. If all three additional specimens pass the test, the cover fabric passes the test. If any one of the additional three specimens fails, the cover fabric fails the test.

DISCUSSION: The current version of California Technical Bulletin 117-2013 has no provision to recognize cigarettes that self-extinguish prior to burning their entire length. However, ASTM E 1353 does recognize this phenomenon.

The Govmark report evaluates replacement cigarettes as follows:

If a cigarette self-extinguishes (SE) before burning its entire length, a new cigarette is placed into the test. If the new (replacement) cigarette self-extinguishes or burns its entire length, the result for that specimen will then be evaluated as if the cigarette burned its entire length when assigning the "Passing/Failure" conclusion.



Page 3

Received:08/2	25/2016	Completed: 08/26/2	2016 Letter: N1	BG <b>P.O.</b> #:		Test Report #:	3-150	049-1-
Client's Identification			ition: 100% Vinyl Kn	it Back, Resilience	Finish. Weight	: 30 oz/lin yard. Pro	duct End Use:	
Cested For: Teesha Prezeau  Designtex  357 County Avenue  Secaucus, NJ 07094					Fabri <b>Tel:</b> 1-(20	TB 117-2013 (Sectionic) /ACT 01)-917-7738 01)-917-7764	n 1-Cover 235  Ext:	235
RESULTS:		Specimen #	Char Length (inches)	SE (yes/no)	SB45 (yes/no	TOF ) (yes/no)		
Initial	. <b>:</b>	1 2 3	0 0 0	Yes Yes Yes	No No No	No No No		
Replace (If nee		1 2 3	0 0 0	Yes Yes Yes	No No No	No No No		
Repeat ( (If nee		1 2 3						<del>,</del>
EXPLANATIO	N:							
Initial:		These are the first 3 cigarettes where the results could be sufficient to draw a test conclusion.						
Replacement:		If any of the initial cigarettes self-extinguish before burning their complete length, a new test is conducted with a fresh cigarette.						
Repeat Test:		Depending on the initial or replacement results, 3 repeat tests might be required to draw a conclusion.						
CODES USED	:							
SB45 = \$ TOF = 5 MNR = 1 EC = 1	Smolde: Transi Measur transi Escala	r beyond 45 min tions to open f ement not recor tioned to open ting smoldering	laming ded as smolderin	g exceeded 45	minutes or a			
CONCLUSION The above indicate	ve res	ults reported f	or the initial a	nd / or replac	ement cigare	ettes are suffi	cient to	
[x] I	Passin	g; [] Failure	; [ ] Repeat tes	t on 3 additio	onal specimen	าร		
The results after conducting the repeat tests indicate:								
[]	Passing	g; [ ] Failure		(Page 3 of 4)				



Page 4

3-15049-1-Received: 08/25/2016 Completed: 08/26/2016 Letter: N1 BG | P.O.#: Test Report #: Client's Style: Rise 3809. Composition: 100% Vinyl Knit Back, Resilience Finish. Weight: 30 oz/lin yard. Product End Use: Identification Upholstery. 235 Key Test: CA TB 117-2013 (Section 1-Cover Tested For: Teesha Prezeau Fabric) /ACT Designtex Tel: 1-(201)-917-7738 357 County Avenue Ext: Fax: 1-(201)-917-7764 Secaucus, NJ 07094

REMARKS: None.

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified above.

AUTHORIZED SIGNATURE

GOVMARK

/pm

Ms. Phyllis Pettit
AUG 3 1 2016

(Page 4 of 4)