

3001 Tilt was tested and met the following flammability requirements:

CA TB 117-2013

ISO/IEC 17025 Third Party Test Report

DATE: April 2, 2021

FILE: DESTEX.A031821G

CLIENT: Design Tex Inc.
200 Varick Street, 8th Floor
New York, NY 10014

ATTN: Teesha Prezeau

SAMPLE IDENTIFIED BY CLIENT AS:

Fabric Submitted

Name: Tilt 3001

Finish: Crypton Epure, Backing: Polyester Woven

100% Polyester (Polycarbonate Blend)

Color Tan/Green/Orange Multi

TEST PROCEDURES:

TEST RESULTS:

CALIFORNIA TECHNICAL BULLETIN 117-2013

SECTION 1 COVER FABRIC TEST

CHAR LENGTH (mm)

Specimen #1: SE
Specimen #2: SE
Specimen #3: SE

SE = Self Extinguished

- a) The mock-up test specimen continues to smolder after the 45-minute test duration: **NO**
- b) A char develops more than 1.8 inches (45 mm) in any direction from the cigarette on the cover fabric measured from its nearest point: **NO**
- c) The mock-up test specimen transitions to open flaming: **NO**

RESULTS: Pass

A material is considered to pass or fail based on the following criteria:

1. A single mock-up test specimen fails to meet the requirements of this test procedure if any of the following criteria occurs:
 - a) The mock-up test specimen continues to smolder after the 45-minute test duration.
 - b) A char develops more than 1.8 inches (45 mm) in any direction from the cigarette on the cover fabric measured from its nearest point.
 - c) The mock-up test specimen transitions to open flaming.
2. The cover fabric passes the test if three initial mock-up specimens pass the test, i.e., the cigarettes burn their full length and the mock-ups are no longer smoldering.
3. If more than one initial specimen fails, the cover fabric fails the test.
4. If any one of the three initial specimens fails, repeat the test on an additional three specimens.
5. If all three additional specimens pass the test, the cover fabric passes the test. If any one of the three additional specimens fails, the cover fabric fails the test.