Flammability Certificate 3012 Velvet Corduroy

Designtex

3012 Velvet Corduroy was tested and met the following flammability requirements:

CA TB 117-2013



Page 1

Received: 11/1	13/2019 C	Completed: 11/15/2019	Letter: M6	BG	P.O.#:	Test Report #:	3	-35548-6-		
Client's		Velvet Corduroy). Conte	ent: 42% Polyeste	er, 589	% Acrylic. Weight: 56	0 g/lm. Color: Olive Gr	een. Product	End Use:		
Identification Upholstery.										
Tested For: Megan Rietzke Key Test: CA TB 117-2013 (Section 1-Cover							275			
J	Designtex					Fabric) /ACT				
	200 Varic	k Street			Tel:	1-(212)-886-8137	Ext:			
	New York	k, NY 10014			Fax:	1-()				

Test Category: Cigarette Ignition Specifier: ACT

LE 2018; V 01/19 NTR 9/15

Product Category: Upholstery

dl/SM PC: 24H

TEST PERFORMED: California Technical Bulletin 117-2013 - Requirements, Test Procedure and Apparatus for Testing the Smolder Resistance of Materials Used in Upholstered Furniture (June 2013 Version; V 1/19)

Section 1, Cover Fabric Test (Upholstery cover material is the outermost layer of fabric or related material used to enclose the main support system or upholstery materials, or both, used in the furniture item.) --

As cited by the ACT Voluntary Performance Guidelines (August 2018)

REFERENCE: ASTM E1353-08ae1

IGNITION SOURCE: Cigarette

SPECIMEN TEST COMPOSITE:

Upholstery Cover Material: As described in "Client's Identification".

Standard Substrate Material: Non FR polyurethane foam, density $1.8 \pm 0.05 \text{ lb/ft}^3$

BRIEF DESCRIPTION OF TEST: Miniature cushions are prepared using the client's cover fabric over the standard filling material. The vertical or back cushions measure 8" x 8" x 2". The horizontal or seat cushions measure 8" x 5" x 2".

A lighted cigarette is placed in the crevice formed by the vertical cushion and the horizontal cushion.

The test is terminated at 45 minutes if smoldering is no longer observed.

Test measurements and observations are recorded.

-- See Page 3 for "Results" and "Conclusion" --

(Page 1 of 4)



Page 2

Received: 11/	13/2019	Completed: 11/15/2019	Letter: M6	BG	P.O.#:		Test Report #	#: 3	-35548-6-
Client's Identificatio		(Velvet Corduroy). Contestery.	ent: 42% Polyeste	er, 58%	% Acrylic.	Weight: 56	0 g/lm. Color: Olive (Green. Product	End Use:
Tested For:	Tested For: Megan Rietzke					Key Test:	CA TB 117-2013 (Se	ection 1-Cover	275
	Designte	ex					Fabric) /ACT		
	200 Var	ick Street				Tel:	1-(212)-886-8137	Ext:	
	New Yo	ork, NY 10014				Fax:	1-()		

PASS/FAIL/REPEAT CRITERIA: A material is considered to pass or fail based on the following criteria:

- 1. A single mock-up test specimen fails to meet the requirements of this test procedure if any of the following criteria occurs:
 - a) The mock-up test specimen continues to smolder after the 45 minute test duration;
 - b) A vertical char length (measured as specified in step 11.9 of ASTM E1353-08ae1) of more than 1.8 inches (45 mm) develops on the cover fabric.
 - c) The mock-up test specimen transitions to open flaming.
- 2. The cover fabric passes the test if three initial mock-up specimens pass the test, i.e., the cigarettes burn their entire length and the mock-ups are no longer smoldering.
- 3. If more than one initial specimen fails, the cover fabric fails the test.
- 4. If any one of the three initial specimens fails, repeat the test on additional three specimens.
- 5. If all three additional specimens pass the test, the cover fabric passes the test. If any one of the additional three specimens fails, the cover fabric fails the test.

DISCUSSION: The current version of California Technical Bulletin 117-2013 has no provision to recognize cigarettes that self-extinguish prior to burning their entire length. However, ASTM E 1353 does recognize this phenomenon.

The SGS Govmark report evaluates replacement cigarettes as follows:

If a cigarette self-extinguishes (SE) before burning its entire length, a new cigarette is placed into the test. If the new (replacement) cigarette self-extinguishes or burns its entire length, the result for that specimen will then be evaluated as if the cigarette burned its entire length when assigning the "Passing/Failure" conclusion.

(Page 2 of 4)



Page 3

teceived: 11/13/2019	Completed: 11/15/	2019 Letter: M6	BG P.O. #:	Te	est Report #:	3-35548-6-
Client's Style: dentification Uphol	177	Content: 42% Polyeste	r, 58% Acrylic. W	eight: 560 g/lm. Co	olor: Olive Gree	n. Product End Use:
			К	Test: CA TB 1 Fabric) / A Tel: 1-(212)-8 Fax: 1-()-	ACT 886-8137	on 1-Cover 27:
RESULTS:	Specimen #	Char Length (inches)	SE (yes/no)	SB45 (yes/no)	TOF (yes/no)	
Initial:	1 2 3	0.6 0.6 0.6	No No No	No No No	No No No	
Replacement: (If needed)	1 2 3					
Repeat Tests: (If needed)	1 2 3					
XPLANATION:						
Initial:	draw a test co					
Replacement:		initial cigarette test is conducted			rning their	complete
Repeat Test:	Depending on to draw a cond	the initial or rep clusion.	lacement resu	lts, 3 repeat	tests might	be required
CODES USED:						
SB45 = Smolde TOF = Transi MNR = Measur transi EC = Escala	r beyond 45 min tions to open : ement not reco: tioned to open ting smoldering	flaming rded as smoldering	exceeded 45	minutes or spe	cimen	
CONCLUSION: The above res indicate:	ults reported	for the initial ar	nd / or replac	ement cigarett	es are suffi	icient to
[x] Passin	g; [] Failur	e; [] Repeat test	on 3 additio	nal specimens		
			. 290 (000 000 100 100 100 100 100 100 100 1			
The results a	fter conducting	g the repeat tests	: indicate:			



Page 4

Received: 11/	13/2019	Completed: 11/15/2019	Letter: M6	BG	P.O.#:	Test Report #:	3-	35548-6-	
Client's		(Velvet Corduroy). Conte	ent: 42% Polyeste	er, 589	% Acrylic. Weight: 56	60 g/lm. Color: Olive Gre	en. Product E	End Use:	
Identification Upholstery. Tested For: Megan Rietzke Key Test: CA TB 117-2013 (Section 1-Cover 275)									
	Designt				·	Fabric) /ACT			
	200 Var	rick Street			Tel:	1-(212)-886-8137	Ext:		
	New Yo	ork, NY 10014			Fax:	1-()			

REMARKS: None.

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified above.

AUTHORIZED SIGNATURE

SGS GOVMARK

/jab /pm

Phyllis Pettit

DEC 0 3 2019

(Page 4 of 4)