

FIORANO
ITALIAN MARBLE

STONESOURCE



FLOOR
GRIGIO Natural 24"x48" Rectified

WALL
GRIGIO Polished 24"x24" Rectified



FLOOR
GRIGIO Natural 24"x48" Rectified

WALL
GRIGIO Rope Mosaic 13"x14.5" Rectified



FLOOR
ORO Natural 12"x24" Rectified

WALL
ORO Polished 4"x12" Rectified



FLOOR

ORO Polished 24"x48" Rectified

WALL

ORO Polished 24"x48" Rectified
ORO Rhomboid Mosaic 12.5"x13.5" Rectified

FIORANO ITALIAN MARBLE

FINE PORCELAIN STONEWARE

COLOR AVAILABILITY



GRIGIO




ORO

SIZE AVAILABILITY



24”x48” Rectified

Thickness: 10mm
Finish: Natural / Polished
Available in all colors



12”x24” Rectified

Thickness: 10mm
Finish: Natural / Polished
Available in all colors



4”x12” Rectified

Thickness: 10mm
Finish: Natural / Polished
Available in all colors

FIORANO ITALIAN MARBLE

FINE PORCELAIN STONEWARE


DECORS

Mosaic 12”x12” (2”x2” Pcs)

Finish: Natural / Polished



GRIGIO



ORO

Muretto Mosaic 12”x12”

Finish: Natural / Polished



GRIGIO



ORO

Hexagon Mosaic 12”x14”

Finish: Natural / Polished



GRIGIO




ORO

Rhomboid Mosaic 12.5”x13.5”

Finish: Natural / Polished



GRIGIO



ORO

FIORANO ITALIAN MARBLE

FINE PORCELAIN STONEWARE

DECORS

Rope Mosaic 13”x14.5”

Finish: Natural / Polished



GRIGIO



ORO

Elongated Mosaic 12”x12”

Finish: Natural / Polished




GRIGIO



ORO

SPECIAL PIECES



Bullnose 3”x24”

Finish: Natural

Available in all colors

TECHNICAL SPECIFICATIONS

PORCELAIN STONEWARE UNI EN 14411 (ISO 13006) Bla (APPENDIX G)

TECHNICAL FEATURE	TEST METHODS	REQUIREMENTS IN ACCORDANCE TO THE STANDARDS	AVERAGE VALUE	
			NATURAL	LAPPATO
Water absorption	ISO 10545-3	≤ 0.5%	≤ 0.10%	
Flexural resistance (R)	ISO 10545-4	Min. 1300N	> 40 N/mm²	
Breaking strength		Thickness: < 7.5mm S ≥ 700N Thickness: ≥ 7.5mm S ≥ 1300N	S > 1700N	
Resistance to surface abrasion	ISO 10545-7	Class 0-5	Class 4	Class 5
Linear expansion thermic coefficient (α)	ISO 10545-8	As Reported	7.5 x 10 ⁻⁶ °C ⁻¹	
Resistance to sudden temperature changes	ISO 10545-9	-	Resistant	
Frost resistance	ISO 10545-12	As Reported	Resistant	
Chemical Resistance	ISO 10545-13	Domestic Chemical Products: UB/GB	GA	
		Acids and Alkalis: As Reported	GLA	GLB
Stain resistance	ISO 10545-14	Minimum: Class 3	Class 4-5	
Slip Values				
D.C.O.F.	ANSI A137.1 2012 BOT 3000	> 0.42 Wet	> 0.42 Wet	-

NOTES:

