

FIORANO
CLASSIC ONYX

STONESOURCE



MILK

HONEY

SILVER



FLOOR
SILVER Natural 12"x24" Rectified

WALL
SILVER Polished 12"x24" Rectified

BATHTUB
SILVER Natural 4"x12" Rectified



LEFT WALL

MILK + SILVER Rope Mosaic Polished 13"x14.5"
MILK Mosaic Polished 12"x12" (2"x2" pcs)

FLOOR

SILVER Natural 8"x47" Rectified

RIGHT WALL

MILK Polished 8"x47" Rectified



FLOOR
MILK Natural 8"x47" Rectified

WALL
MILK Rhomboid Mosaic Natural 12.5"x13.5"



HONEY Natural 8"x47" Rectified



FLOOR
HONEY Polished 12"x24" Rectified

WALL
HONEY Elongated Hexagon Mosaic Polished 12"x12"

FIORANO CLASSIC ONYX

PORCELAIN

COLOR AVAILABILITY



MILK



SILVER




HONEY

SIZE AVAILABILITY



12”x24” Rectified

Thickness: 10mm
Finish: Natural/Polished
Available in all colors



8”x47” Rectified

Thickness: 10mm
Finish: Natural/Polished
Available in all colors



4”x12” Rectified

Thickness: 10mm
Finish: Natural/Polished
Available in all colors


FIORANO CLASSIC ONYX

PORCELAIN

DECORS

Mosaic 12”x12” (2”x2” Pcs)

Finish: Natural/Polished



MILK



HONEY



SILVER

Muretto 12”x12”

Finish: Natural/Polished



MILK



HONEY



SILVER

Hexagon Mosaic 12”x14”

Finish: Natural/Polished



MILK



HONEY



SILVER

Rhomboid Mosaic 12.5”x13.5”

Finish: Natural/Polished



MILK



HONEY



SILVER


FIORANO CLASSIC ONYX

PORCELAIN

DECORS

Rope Mosaic 13”x14.5”

Finish: Natural/Polished



MILK




HONEY




SILVER

Elongated Hexagon Mosaic 12”x12”


Finish: Natural/Polished



MILK




HONEY



SILVER

SPECIAL PIECES



Bullnose 2.75”x24”

Finish: Natural/Polished
Available in all colors

FIORANO CLASSIC ONYX

PORCELAIN

TECHNICAL CHARACTERISTICS

TECHNICAL CHARACTERISTICS	REFERENCE STANDARD	STANDARD REQUIREMENTS	TEST RESULTS	
			NATURAL	POLISHED
Water Absorption	UNI EN ISO 10545-03	< 0.5%	E <0.1%	
Breaking Strength	UNI EN ISO 10545-04	Minimum: 1300N	> 1700	
Modulus of Rupture	UNI EN ISO 10545-04	Minimum: 35N/mm²	> 40	
Resistance to abrasion of glazed tiles (PEI)	UNI EN ISO 10545-07	See manufacturer’s declaration	MILK: Class 5 HONEY: Class 4 SILVER: Class 4	MILK: Class 4 HONEY: Class 4 SILVER: Class 4
Thermal Linear Expansion	UNI EN ISO 10545-08	As reported	7.5 x 10 ⁻⁶ / °c	
Thermal Shock Resistance	UNI EN ISO 10545-09	-	Resistant	
Frost Resistance	UNI EN ISO 10545-12	As reported	Resistant	
Chemical Resistance	UNI EN ISO 10545-13	Domestic Chemical Products: UB/GB	GA	
		Acids and Alkalis: As reported	GLA-GLB	GLB
Stain Resistance	UNI EN ISO 10545-14	Minimum: Class 3	Class 4-5	Class 3-4
MOHS	-	-	7	4
Dynamic Coefficient of Friction (DCOF)	ANSI A137.1	≥ 0.42 Wet	≥ 0.42 Wet	-
Friction Coefficient (Slipperiness)	DIN 51130	-	R9	-
Shade Variation	Not Available	As reported	V2	
Thickness	UNI EN ISO 10545-02	As reported	±5%	
Number of Screens	Not Available	As reported	8”x47”: 30 Screens 12”x24”: 40 Screens 4”x12”: 240 Screens	

SHADE VARIATION V2

≥ 34% RECYCLED CONTENT

FREIGHT SOLUTIONS

