TOTO

MW6424726CUFG(A)

Nexus® 1G® WASHLET®+ S7 One-Piece Toilet - 1.0 GPF

FEATURES

- Concealed supply connection for seamless installation
- Ultra high-efficiency TORNADO FLUSH_® system -1.0 GPF (3.8 LPF)
- CEFIONTECT® ceramic glaze minimizes waste from sticking to porous ceramic surfaces
- Completely skirted design for a sleek and understated look that's easier to clean
- Universal Height
- Chrome plated trip lever
- 12" Rough-in
- Elongated front bowl and WASHLET+ S7 and tank set
- EWATER+® auto-cleans wand and bowl after every use
- PREMIST® automatically mists the bowl before each use
- Multifunction pearl white block-style remote control
- Night light
- Auto flush available as upgrade

MODELS

MW6424726CUFGA (#01)

With CEFIONTECT ceramic glaze, WASHLET+ S7 with contemporary design and Auto Flush

- CST642CUFGAT40
 Elongated bowl with CEFIONTECT
- **SW4726AT40** WASHLET+ S7
- **THU856**Auto Flush Kit
- MW6424726CUFG (#01)

Same as MW6424726CUFGA without Auto Flush

OPTIONAL COMPONENTS

- TSU10W.14
 - 14" Unifit Rough-In
- THU485(#01, #BN, #PN, #MBL)

Trip Lever - Cotton, Brushed Nickel, Polished Nickel, Matte Black

COLORS/FINISHES

#01 Cotton



One Gallon Per Flush UNIVERSAL HEIGHT

TORNADO FLUSH



CEFIONTECT



PRODUCT SPECIFICATION

The one-piece ultra high-efficiency TORNADO FLUSH system toilet shall be 1.0 GPF (3.8 LPF). Toilet shall be 12" Unifit rough-in. Toilet shall have optional CEFIONTECT ceramic glaze and be at Universal Height. Toilet shall have elongated front bowl with SoftClose seat and Polished Chrome trip lever.

Toilet shall be TOTO Model MW6424726CUFG___#01.

See SW4726AT40 Specification Sheet for details on included WASHLET.

CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO (cUPC_®), EPA WaterSense_®, State of Massachusetts, City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California AB715, California Green Building Code, City of Los Angeles Water Efficiency Ordinance, and others
- ADA compliant for residential use with autoflush feature model, or with trip lever located on the approach side
- Complies with CA Prop 65 warning requirements







SPECIFICATIONS

Water Use	1.0 GPF (3.8 LPF)
Flush System	TORNADO FLUSH®
Min. Water Pressure	8 psi (Flowing)
Water Surface	6-5/8" x 9-1/8"
Trap Diameter	2-1/8"
Rough-in	12" (14" option available)
Trap Seal	2-1/8"
Warranty	One Year Limited Warranty
Material	Vitreous China
Shipping Weight	CST642CUFGAT40: 110 lbs SW4726AT40: 14.5 lbs
Shipping Dimensions	CST642CUFGAT40 29-1/2" L x 18-1/2" W x 27-1/2" H ² x 21-3/4" H ¹ SW4726AT40 23-3/8" L x 17-5/8" W x 6-1/4" H


See SW4726AT40 Specification Sheet for details on included WASHLET.

DIMENSIONS

INSTALLATION NOTES


Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



To maintain adequate wall gap between the back of the tank and wall, mount the floor flange at a nominal 12" rough-in distance.

Ultra-low high efficiency toilets require a system with adequate supplemental flows from other water usage fixtures and a 4" ID drainline with minimum 2% slope and maximum linear runs of 60ft.





These dimensions and specifications are subject to change without notice