

# FORMWORK

## Formwork

Broadloom

### Construction

Tufted, Level Loop

### Broadloom Width

13'6" (4.11 m)

### Yarn Type

Universal Fibers® Solution-Dyed Nylon Type 6,6

### Stain Repel / Stain Resist / Soil Release

StainSmart®

### Dye Method

Solution Dyed

### Tufted Face Weight

18 oz/yd<sup>2</sup> (610.3 g/m<sup>2</sup>)

### Gauge

1/10

### Stitches Per Inch

11.0

### Tufts

110/in<sup>2</sup> (1,704/100 cm<sup>2</sup>)

### Finished Pile Height

0.15" (3.81 mm)

### Average Density (Finished)

6,300

### Standard Backing

Endura-Loc™

Available with Cushion-Loc™ attached cushion

### Nominal Total Thickness

0.25" (6.4 mm)

### Nominal Total Weight

55.0 oz/yd<sup>2</sup> (1,865 g/m<sup>2</sup>)

### Flammability (Radiant Panel ASTM-E-648)

≥ 0.45 (Class I)

### Smoke Density (NFPA-258-T or ASTM-E-662)

≤ 450

### Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)

Self-Extinguishing

### Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

### Crocking (AATCC 165)

≥ 4.0 Wet or Dry

### Static Electricity (AATCC-134) 20% R.H., 70° F.

≤ 3.5 KV, Solution Dyed

### Texture Appearance Retention Rating (TARR)

Heavy Traffic End-Use Applications

### Recommended Maintenance

MilliCare® Textile and Carpet Care Service Network

### Indoor Air Quality—CRI Green Label Plus™

GLP2860, Carpet Category 1Y

## WARRANTIES

10 Year Face Fiber Wear

10 Year Delamination of Backing

10 Year Antistatic

10 Year Edge Ravel

5 Year Matting and Crushing

10 Year Tuft Bind

Lifetime Staining/Soiling (StainSmart®)

10 Year Colorfastness

Flammability



Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.