SPECIFICATION SHEET Date: 01.08.2024 Revision 13

NORDIC STORIES

Hidden Plains



Construction	Tufted, Textured Loop Pile
Face Fibre	Solution Dyed Nylon (20% recycled content)
Stain Resist	Inherently stain resistant fibre
Finished Face Weight	595 g/m ²
Gauge	47.2 / 10 cm
Rows	38 / 10 cm
Tuft Density	179,528 /m²
Finished Pile Height	3.3 mm
Standard Backing	WellBAC $^{\$}$ Comfort 90% recycled open cell polyurethane cushion backing. Available with TractionBack $^{\$}$ on request
Nominal Total Thickness	8.9 mm
Tile Size	50 cm x 50 cm
Nominal Total Weight	4100 g/m ²
Tiles per Box	20 (5m²)

n	_	n	_	$\hat{}$	ъ	A 4	N	IC	г

Flammability (Euroclassification EN13501:1-2018)	Class BfI - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Castor Chair (BS EN 985:2001)	Class A - Intensive use (r value \geq 2.4)
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	30 dB ΔL_{w}
Sound Absorption (ISO354)	0.25 (H) Class E
Alpha p values	125Hz 0.00, 250Hz 0.05, 500Hz 0.35, 1000Hz 0.20, 2000Hz 0.30, 4000Hz 0.40

ENVIRONMENTAL

59% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

M/PACT Carbon Neutral Floors, 7.53 kg CO2 e/m2 Embodied Carbon (EPD calculation A1-A3) Cradle to Gate footprint 100% off set

WARRANTIES

12 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIF	CERTIFICATIONS												
7	K Z			(S)				bsi. ISO MACOR 2015 Itwa age said	ISO 190012015 Quality Management	ISO SOOOI Energy Management	BRE/Global Verified ELS		
CRICAL CONTROL OF THE	CARPETE IN THE STATE OF THE STA	FRESCONS DANS LIGHT INTERBURANT A+ A B C	PROFI CONTROL OF THE PROFIT OF	EPD LIST SHE THE LIST CONTROL OF THE PROPERTY	EM1> 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	M/PACT	cradiatocrade	Red List Free					



