

# TEXTURED SKY

## Rainmaker – Eco Low Embodied Carbon Version

Modular Tile

### Construction

Tufted, Textured Loop

### Tile Size

50 cm x 50 cm (19.7" x 19.7")

25 cm x 1 m (9.84" x 39.4")

### Yarn Type

ECONYL® Recycled Nylon

### Stain Resist / Soil Release

StainSmart®

### Dye Method

Solution Dyed

### Tufted Face Weight

28.0 oz/yd<sup>2</sup> (949.4 g/m<sup>2</sup>)

### Gauge

1/12

### Stitches Per Inch

10.4

### Tufts

124.8/in<sup>2</sup> (1,933/100 cm<sup>2</sup>)

### Finished Pile Thickness

0.120" (3.05 mm)

### Average Density (Finished)

8,229

### Standard Backing

PVC-Free WellBAC® Comfort Plus Cushion

Available with TractionBack®

### Recycled Content by Total Weight

Standard Backing: 57.1% Pre-Consumer, 0.0% Post-Consumer  
NSF 140 Platinum Backing Option: 48.3% Pre-Consumer, 8.8% Post-Consumer

### Embodied Carbon

9.8 (kg CO<sub>2</sub>e)/m<sup>2</sup>

### Nominal Total Thickness

0.380" (9.7 mm)

### Nominal Total Weight

119.0 oz/yd<sup>2</sup> (4,035 g/m<sup>2</sup>)

### Flammability (Radiant Panel)

**ASTM-E-648**

≥ 0.45 (Class I)

### Smoke Density (NFPA-258-T or

**ASTM-E-662)**

≤ 450

### Methenamine Pill Test (CPSC FF-1-70

**or ASTM D 2859**

Self-Extinguishing

### Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

### Crocking (AATCC 165)

≥ 4.0 Wet or Dry

### Static Electricity (AATCC-134) 20%

**R.H., 70° F.**

≤ 3.5 KV, Permanent Conductive Fiber

### Texture Appearance Retention Rating (TARR)

Heavy Traffic End-Use Applications

### Recommended Maintenance

MilliCare® Textile and Carpet Care Service Network

### Indoor Air Quality—CRI Green Label Plus™

GLP7205, Carpet Category 13X

### Recommended Installation Method(s)

Monolithic, Ashlar, Planks

### WARRANTIES

Lifetime Face Fiber Wear

Lifetime Antistatic

Lifetime Floor Compatibility

Lifetime Color Pattern Permanency

Lifetime Floor Release

Lifetime Cushion Resiliency

Lifetime Moisture Resistance

Lifetime Delamination of Backing

Lifetime Staining/Soiling (StainSmart®)

Lifetime Dimensional Stability

Lifetime Tuft Bind

Lifetime Edge Ravel

Flammability



**Declare.**



This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.