

OBEX™ IDENTITY TILE: CUT

Entrance Flooring

Construction

Tufted, Cut Pile

Tile Size

1 m x 1 m (39.4" x 39.4")

Yarn Type

Milliken-Certified WearOn® Nylon and Monofilament

Dye Method

PrintWorks™ Precision Dye

Tufted Face Weight

28 oz/yd² (949 g/m²)

Gauge

5/32

Stitches Per Inch

5.6

Tufts

35.8/in² (554/100 cm²)

Finished Pile Height

0.182" (4.62 mm)

Average Density (Finished)

5,281

Standard Backing

PVC-Free WellBAC® Comfort Plus Cushion

Available with TractionBack®

Recycled Content by Total Weight

36.2% Pre-Consumer,
0.0% Post-Consumer

Embodied Carbon

21.15 (kg CO₂e)/m²

Nominal Total Thickness

0.50" (12.7 mm)

Nominal Total Weight

130 oz/yd² (4,407 g/m²)

Flammability (Radiant Panel

ASTM-E-648)

≥ 0.45 (Class I)

Smoke Density (NFPA-258-T or

ASTM-E-662)

≤ 450

Methenamine Pill Test (CPSC FF-1-70

or ASTM D 2859

Self-Extinguishing

Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

Crocking (AATCC 165)

≥ 4.0 Wet or Dry

Static Electricity (AATCC-134) 20% R.H., 70° F.

≤ 3.5 KV, Permanent Conductive Fiber

Recommended Maintenance

Daily Vacuum, Deep Clean via Hot Water Extraction

Indoor Air Quality—CRI Green Label Plus™

GLP7205, Carpet Category 13X

Recommended Installation Method(s)

Monolithic

Installation Zone Application

Zone 2 or Zone 3

ADA / BS8300 / ISO 21542 Compliant

WARRANTIES

Lifetime Face Fiber Wear

Lifetime Antistatic

Lifetime Floor Compatibility

Lifetime Color Pattern Permanency

Lifetime Floor Release

Lifetime Cushion Resiliency

Lifetime Moisture Resistance

Lifetime Delamination of Backing

Lifetime Staining/Soiling (StainSmart®)

Lifetime Dimensional Stability

Lifetime Tuft Bind

Lifetime Edge Ravel

This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.



Find us in
MasterSpec®
Powered by Delttek Specpoint®