

# OBEX™ GRID: CUTX

11mm Closed

Entrance Flooring

## MODULAR GRID

### Grid Material

100% UV-Resistant PVC

### Grid Size

Nominal: 7.87" x 7.87" (200 mm x 200 mm)

Installed Usable: 7.80" x 7.80" (198 mm x 198 mm)

### Total Nominal Thickness

11 mm (0.43")

### Grid Color

Black

### Temperature Resistance

-22°F to +122°F (-30°C to +50°C)

## TEXTILE

### Construction

Tufted, Cut Pile

### Yarn Type

Milliken-Certified WearOn® Nylon and Monofilament

### Dye Method

PrintWorks™ Precision Dye

### Tufted Face Weight

24 oz/yd² (814 g/m²)

### Nominal Total Weight

28.8 oz/ft² (8,800 g/m²)

### Flammability (Radiant Panel ASTM-E-648)

≥ 0.45 (Class I)

### Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)

Self-Extinguishing

### Lightfastness (AATCC 16E)

≥ 4.0 at 80 hours

### Crocking (AATCC 165)

≥ 4.0 Wet or Dry

### Recommended Maintenance

Daily Vacuum, Deep Clean via Hot Water Extraction

### Rolling Load (ASTM F2753)

No noticeable deformation or damage to the structural integrity with a 400 pound per wheel at 2,500 cycles with load applied to a 200 mm diameter, 32 mm wide rubber tread castor.

### Grids Per Box

30 Pieces, 12.66 ft² (1.18 m²)

### Installation Zone Application

Zone 2

ADA / BS8300 / ISO 21542 Compliant

## WARRANTIES

1 Year Manufacturing Defect Warranty

5 Year Wear Warranty



Find us in

**MasterSpec®**

Powered by Deltek Specpoint®