

OBEX™ TILE: LOOP

Entrance Flooring

Construction

Tufted, Multi-Level Loop

Tile Size

50 cm x 50 cm (19.7" x 19.7")

Yarn Type

ECONYL® Solution-Dyed Nylon and Solution-Dyed Nylon Monofilament

Dye Method

Solution Dyed

Tufted Face Weight

27.9 oz/yd² (946 g/m²)

Gauge

1/12

Stitches Per Inch

11.3

Tufts

135.6/in² (2,100/100 cm²)

Finished Pile Height

0.255" (6.48 mm)

Average Density (Finished)

5,740

Standard Backing

PVC-Free WellBAC® Comfort Cushion
Available with TractionBack®

Recycled Content by Total Weight

33.3% Pre-Consumer,
6.6% Post-Consumer

Embodied Carbon

8.89 (kg CO₂e)/m²

Nominal Total Thickness

0.391" (9.9 mm)

Nominal Total Weight

104.2 oz/yd² (3,533 g/m²)

Flammability (Radiant Panel

ASTM-E-648)

≥ 0.45 (Class I)

Smoke Density (NFPA-258-T or

ASTM-E-662)

≤ 450

Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859

Self-Extinguishing

Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

Crocking (AATCC 165)

≥ 4.0 Wet or Dry

Static Electricity (AATCC-134) 20% R.H., 70° F.

≤ 3.5 KV, Permanent Conductive Fiber

Recommended Maintenance

Daily Vacuum, Deep Clean via Hot Water Extraction

Indoor Air Quality—CRI Green Label Plus™

GLP7205, Carpet Category 13X

Recommended Installation Method(s)

Monolithic, Quarter-Turn, Ashlar

Pieces Per Box

12 Tiles, 32.29 ft² (3.0 m²)

Installation Zone Application

Zone 2 or Zone 3

ADA / BS8300 / ISO 21542 Compliant

WARRANTIES

Lifetime Face Fiber Wear
 Lifetime Antistatic
 Lifetime Floor Compatibility
 Lifetime Color Pattern Permanency
 Lifetime Floor Release
 Lifetime Cushion Resiliency

Lifetime Moisture Resistance
 Lifetime Delamination of Backing
 Lifetime Staining/Soiling (StainSmart®)
 Lifetime Dimensional Stability
 Lifetime Tuft Bind
 Lifetime Edge Ravel

This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.




Find us in
MasterSpec®
 Powered by Delttek Specpoint®