Specifications Tek-Wall 1003 300089

maharam

Application

Upholstered Walls, Walls

Characteristics

Content: 62% Solution-Dyed Polyolefin, 38% Polyester

Finish: Stain Repellent Backing: Acrylic Width: 56" (142cm) Bolt Size: 40 yards (37 m) Weight: 17.5 oz/ly (543 gr/lm)

Traffic: High-Suitable for all applications including heavy duty.

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Contact your sales representative for pricing. A cutting charge applies for orders under 40 yards.

Maintenance

W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach. $\boxtimes \Delta \boxtimes \boxtimes \Theta$

Testing

Acoustics: ASTM C423, 0.75 NRC

Flammability: AS/NZS 3837 Adhered ASTM E84 Adhered ASTM E84 Unadhered CAN ULC S102 Adhered CAN ULC S102 Unadhered EN 13501 Adhered* EN 13501 Unadhered* GB 8624 Adhered* GB 8624 Unadhered* ISO 5660 Adhered

*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours



1.25

Specifications Tek-Wall 1003 300089

maharam

Environmental

Greenguard Gold Certified REACH Compliant FR Free

Warranty

10 years: Walls

3 years: Upholstered Walls.

© 2022 Maharam

Complete product information at maharam.com 800.645.3943



025 Riddle