

Specifications
Alphabet
by Alexander Girard®, 1952
300092

maharam

Application

Walls

Characteristics

Content: 100% Cellulose

Finish: None

Backing: 84% Polyester, 16% Post-Consumer Recycled Polyester

Width: 52" (132cm)

Repeat: 11 ½" V, 52" H (29cm V, 132cm H)

Bolt Size: 30 yards (27 m)

Weight: 8.5 oz/ly (264 gr/lm)

Traffic: Moderate-Suitable for heavy duty applications with the exception of high traffic corridors.

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Contact your sales representative for pricing.

A cutting charge applies for orders under 30 yards.

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

CAN ULC S102 Adhered

EN 13501 Adhered*

ISO 5660 Adhered

*passes with additional treatment

Lightfastness: AATCC 16.3, 40+ hours



Specifications

Alphabet

by Alexander Girard®, 1952

300092

maharam

Environmental

Greenguard Gold Certified

LBC Red List Free

REACH Compliant

Contains Bio-Based Content

FR Free

Free of Intentionally Added PFAS

Warranty

3 years.

© 2021 Girard Studio, LLC, Maharam under license

Complete product information at maharam.com

800.645.3943



001 Raw Umber On White 002 Yellow On Light Gray 003 Crimson On White 004 Magenta On Light Gray 005 Ultramarine On Light Gray 006 Turquoise On White



007 Gray Dark On Light Gray