Specifications
6/15/20
300101

# maharam

## **Application**

Walls

#### **Characteristics**

Content: 65% Cellulose, 35% Latex Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' x 16' 8" (305cm x 508cm)

Customs: Repeatable, Scalable Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

## Price

Contact your sales representative for pricing.

#### Maintenance

W-Clean with water-based cleanser.

## **Testing**

Flammability: AS/NZS 3837 Adhered ASTM E84 Adhered CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 40+ hours

\* \* \*

Specifications
6/15/20
300101

## maharam

#### **Environmental**

Greenguard Gold Certified LBC Red List Free Contains Bio-Based Content FR Free Free of Intentionally Added PFAS

#### **Brief**

6/15/20 is based on a work by Sanou Oumar that is part of a series of daily drawings, each created in a single sitting and named for the day it was made. Setting freehand filigree against hard-edged geometry, 6/15/20 reflects the artists' interest in repetition, color, and intricate line work as a transformative healing practice. Despite the complexity of each composition, Oumar's works have no underdrawing, preparatory sketch, or mapping.

### Warranty

3 years.

© 2021 Sanou Oumar, Maharam under license

Complete product information at maharam.com 800.645.3943



001