

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: None

Backing: Polyester / Cotton Osnaburg

Width: 54" (137cm)

Repeat: Non-match

Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (620 gr/m)

Traffic: High-Suitable for all applications including heavy duty.

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Contact your sales representative for pricing.

A cutting charge applies for orders under 30 yards.

Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.



Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

BS 476 Adhered*

CAN ULC S102 Adhered

EN 13501 Adhered*

GB 8624 Adhered*

*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours



Specifications

Filigree

300040

maharam

Environmental

Greenguard Certified

FR Free

Free of Intentionally Added PFAS

Non-Phthalate Vinyl

Warranty

10 years.

© 2019 Maharam

Complete product information at maharam.com

800.645.3943



001 Halo



002 Avant



003 Fleck



004 Empath



005 Delicata



006 Bastion



007 Dashboard



008 Divine



009 Culotte



010 Cupola



011 Gamboge



012 Buccaneer



013 Tartan




014 Syrah



015 Synapse



016 Boulevard



017 Katana



019 Wayfinder



020 Elysium



021 Leeward



022 Chlorophyll




023 Ornate




024 Victor



025 Macropod



026 Sire



027 Bantam