

Faucet Accessories Rough In Valve # GK0900001U00

| < 6 1/2 " > |



Rough In Valve	Dimension	Weight	Order number
Shut-off valve: Yes			
Colors			
00 White			
Variant			
Installation Type: For concealed installation, Dimensions of water supply connection: 3/4 ", cUPC listed: Yes	6 1/2 "x6 1/2 "	3.086 lb	GK0900001U00
Required accessories			
Shower Trim Number of outlets: 2, Water supply connection type: Rough In Valve, Thermostat cartridge, Temperature block (100.4 °F), Selection: Hand shower, Showerhead, Diverter: Shut-off and diverter valve, Number of outlets: 2, recommended operating pressure: 14.5038 - 72.519 psi, Flow rate: 5.44 gal/min, Escutcheon shape: Square, Including functional unit, Including trim parts	5 7/8 x 3 3/4 "	3.968 lb	C14200013
Shower Trim Number of outlets: 2, Water supply connection type: Rough In Valve, Thermostat cartridge, Temperature block (100.4 °F), Selection: Tub filler, Hand shower, Diverter: Shut-off and diverter valve, Number of outlets: 2, recommended operating pressure: 14.5038 - 72.519 psi, Flow rate: 5.44 gal/min, Escutcheon shape: Square, Including functional unit, Including trim parts	5 7/8 x 3 3/4 "	4.189 lb	C15200013
Shower Trim Number of outlets: 2, Water supply connection type: Rough In Valve, Thermostat cartridge, Temperature block (100.4 °F), Selection: Hand shower, Showerhead, Diverter: Shut-off and diverter valve, Number of outlets: 2, recommended operating pressure: 14.5038 - 72.519 psi, Flow rate: 5.44 gal/min, Escutcheon shape: Round, Diameter escutcheon: 6 3/4 ", Including functional unit, Including trim parts	6 3/4 x 3 3/4 "	3.968 lb	C14200014

Faucet Accessories Rough In Valve # GK0900001U00

|< 6 1/2 " >|

Shower Trim Number of outlets: 1, Water supply connection type: Rough In Valve, Thermostat cartridge, Temperature block (100.4 °F), Diverter: Shut-off valve, Number of outlets: 1, recommended operating pressure: 14.5038 - 72.519 psi, Flow rate: 5.44 gal/min, Escutcheon shape: Square, Including functional unit, Including trim parts	5 7/8 x 3 3/4 "	3.968 lb	C14200015
Shower Trim Number of outlets: 1, Water supply connection type: Rough In Valve, Thermostat cartridge, Temperature block (100.4 °F), Diverter: Shut-off valve, Number of outlets: 1, recommended operating pressure: 14.5038 - 72.519 psi, Flow rate: 5.44 gal/min, Escutcheon shape: Round, Diameter escutcheon: 6 3/4 ", Including functional unit, Including trim parts	6 3/4 x 3 3/4 "	3.968 lb	C14200016
Shower Trim Number of outlets: 2, Water supply connection type: Rough In Valve, Thermostat cartridge, Temperature block (100.4 °F), Selection: Tub filler, Hand shower, Diverter: Shut-off and diverter valve, Number of outlets: 2, recommended operating pressure: 14.5038 - 72.519 psi, Flow rate: 5.44 gal/min, Escutcheon shape: Round, Diameter escutcheon: 6 3/4 ", Including functional unit, Including trim parts	6 3/4 x 3 3/4 "	3.968 lb	C15200014

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.

