


ME by Starck Wall Mounted Toilet # 2510092092

| < 14 1/8 " > |



Wall Mounted Toilet	Dimension	Weight	Order number
HygieneGlaze, Flush water quantity: 1.28/1.28 gal, Washdown model, Flushing rim: Rimless, Flush system: washdown model, Outlet horizontal, Concealed fixation, cUPC listed: Yes			
Colors			
20 HygieneGlaze (an antibacterial ceramic glaze that provides almost indefinite effectiveness)			
Variant			
White High Gloss, Flush water quantity: 1.28/0.8 gal, WaterSense: Yes, ADA: Yes	14 1/8 "x16 5/8 "	49.163 lb	2510092092
Infobox			
Not available in Wondergliss			
Spare parts			
Installation Set	5 3/8 x 4 1/8 "	0.948 lb	005072
Actuator Plate A1 Plastic, Dual Flush, Trip lever type: Mechanical, Flush operation technology: Manual, Installation Type: surface mounted, Includes mounting frame, including mounting kit, Includes push rod	8 1/2 x 3/8 "	0.69 lb	WD5008
Connection Set Shower-toilets	8 5/8 x 2 3/8 "	0.617 lb	100731
Mounting Bracket Suitable for Bidet, Wall Mounted Toilet	Ø 1/2 "	0.11 lb	006500
Suitable products			
Shower toilet seat Plus Number of warm air dryer options: 4 Steps, Water position adjustment: 5 Steps, Number of spray intensity options: 3 Steps, Number of spray temperature options: 4 Steps, Water position adjustment: 5 Steps, Rearwash, 14 7/8 x 22 1/2 " Frontwash, Pulsing shower spray: Oscillating, Self-cleaning function, Decalcification function, Energy saving mode: Adjustable, Holiday mode, Night light, 14 7/8 x 22 1/2 "			612000

ME by Starck Wall Mounted Toilet # 2510092092

|< 14 1/8 " >|

Shower toilet seat Lite Number of warm air dryer options: 4 Steps, Water position adjustment: 5 Steps, Number of spray intensity options: 3 Steps, Number of spray temperature options: 4 Steps, Water position adjustment: 5 Steps, Rearwash, 14 7/8 x 22 1/2 " Frontwash, Pulsing shower spray: Oscillating, Self-cleaning function, Decalcification function, Energy saving mode: Adjustable, Holiday mode, Night light, 14 7/8 x 22 1/2 "	612001
In-Wall Tank & Carrier Standard Includes HDPE toilet wall-mounted outlet bend DN 90/90, Powder-coated, Installation Type: In lightweight stand construction, Installation Type: Drywall, Max. projection toilet: 24 5/8 ", Adjustable height: 9 1/2 " 23 1/4 x 3 1/2 " ", Trip lever type: Mechanical, Trip lever placement: Front, Adjustable flush volumes, Flush type: Dual Flush, Insulated tank, Self-supporting, Suitable for panelling with plasterboards, 23 1/4 x 3 1/2 "	WD1022

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.