

Name
Color Fuse

Designer
Suzanne Tick

Style No.
4070


Use
Upholstery

Content
Coating:
100% Polycarbonate Polyurethane
Polyurethane
Base Cloth:
100% Cotton Woven


Abrasion
Martindale
100,000 cycles




Emulsion 4070-02




Plasma 4070-09




Solvent 4070-08




Molten 4070-07



Enamel 4070-04



Freeze 4070-06



Liquefy 4070-05

Name **Color Fuse**

Style No. **4070**

Designer Suzanne Tick

Specification

Use: Upholstery
Content: Coating: 100% Polycarbonate Polyurethane
Base Cloth: 100% Cotton Woven
Weight: 24.51 oz per linear yard
Width: 55"
Pattern Repeat: None
Directional: No

Performance

Abrasion: ASTM D4966 Martindale 100,000 cycles
Adhesion of Coating: ASTM D751 Warp 11.9 lbf, Fill 12.6 lbf
Tear Strength: ASTM D2261 Warp 71.7 lbf, Fill 56.5 lbf
Hydrolysis Resistance: ISO 1419, 10 weeks
Colorfastness to Light: AATCC 16, Grade 5 at 200 Hours
Colorfastness to Crocking: AATCC 8, Wet Class 5, Dry Class 5

Flame Retardancy Cal TB 117-2013

Maintenance W, Clean with a water-based cleaning agent. Do not use solvent products.

Origin Italy

Dye lots may vary slightly from samples shown. Samples shown off the bolt.



Canada
877.705.LUUM
luumtextiles.ca

USA
877.705.LUUM
luumtextiles.com

International
919.464.2922
luumtextiles.com

cdn/us/int/05-19

© Luum™ 2019, all rights reserved.

*,™ Trademarks used under license by Luum™, Color Fuse™

*Certification Marks owned by the Association for Contract Textiles, Inc.

U10 - SC-305-4070