

Style	BioSpec® SR
Construction	Homogeneous Slip Resistant Sheet (Non-ortho phthalate construction)
Classification	ASTM F1913 Sheet Vinyl Floor Covering without Backing
Total Thickness	0.080" (2.03 mm)
Wear Layer	Quantum Guard Elite®
Width	6'6" (2 m)
Colors	12
Pattern Repeat	Random repeat, reverse sheet for seaming
Packaging	30-73 yd² (25.1-61.04 m²) (73 yd² roll is approx. 100 lineal feet)
Weight	6.5 lbs/yd² (2.948 kg/m²)
Adhesive	<p>Porous &amp; Non-porous Substrates:</p> <p>V-88 Full Spread</p> <p>V-95 Full Spread, 2-part Epoxy</p> <p>MoistureLoc Full Spread, One-Component</p> <p>XpressStep for LVT &amp; Sheet Vinyl Full Coverage Spray</p> <p><b>Note:</b> Must use V-95, MoistureLoc, QuickStix or XpressStep adhesive under hospital booms and heavy rolling loads areas. In more abusive conditions such as areas subject to dragging force, direct sunlight or where topical moisture would be a concern, only V-95, MoistureLoc or QuickStix should be used.</p>
QuickStix®	Available with QuickStix® pre-applied adhesive, reducing time and labor required to install the flooring. QuickStix® floors can be used immediately after installation, even in extreme moisture areas.
Seam Method	<p>Mannington Commercial Weld Rods or MLG 33 Chemical Seam Sealer. Mannington Seam Coater Pen for high traffic areas.</p> <p><b>Note:</b> Heat welding is the recommended procedure for healthcare and high traffic applications.</p>
Testing	
HUD/FHA	Meets / Exceeds
ADAG (American Disability Act Guidelines)	Passes
Flexibility (ASTM F137)	Passes - 11/2" Mandrel - No Crack/Break
Static Load (ASTM F970)	Passes - Residual Indent ≤ 0.005"
Static Load (ASTM F970 mod.)	Passes - 2,000 PSI; Residual Indent ≤ 0.005"
Rolling Resistance/Coster Chair (ISO 4918)	25,000 Cycles, No Significant Change
Short Term Residual Indentation (ASTM F1914/F1303)	Passes - Must be < 0.007"
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm²
Smoke Density (ASTM E662)	Passes - ≤ 450
Slip Resistance (ASTM C1028, Dry)	Passes - ≥ 0.5 Leather; 0.6 Rubber
Acoustic IIC (ASTM E492)	50 - 6" Concrete with Drop Ceiling
Acoustic STC (ASTM E90)	63 - 6" Concrete with Drop Ceiling
Resistance to Light (ASTM F1515)	Passes - < 8 Delta E Color Change
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change
Environmental Data	
Indoor Air Quality	FloorScore Certified; CDPH v12-2017
Product Declarations	Third party verified EPD, HPD
Carbon Offset	105% Cradle to Gate (A1-A3), see website for additional information May
LEED	<p>contribute to LEED credits:</p> <p>Building Product Disclosure &amp; Optimization - EPDs</p> <p>Building Product Disclosure &amp; Optimization - Sourcing Raw Materials; Building</p> <p>Product Disclosure &amp; Optimization - IEQc2 - Low Emitting</p>
mindful MATERIALS	Materials Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information
Manufacturing	Salem, NJ (USA) - ISO 14001 EMS & ISO 9001 QMS Registered, +Vantage Vinyl Verified Silver
Warranty	
	Limited 5-Year Commercial Warranty
	Limited 5-Year Quantum Guard Elite® Wear Warranty

**Note:** Visual/Color variations can occur from roll to roll. This variation does not affect product performance. Dye lot maximum of 1000SY.