

Color Anchor Stair Tread Collection

Style	ColorSpec® Stair Tread	ColorSpec® Stair Tread with Visually Impaired Strip
Construction	Thermoset Vulcanized Rubber - Type TS	Thermoset Vulcanized Rubber - Type TS
Classification	ASTM F2169 Class II, Group 1 & 2	ASTM F2169 Class II, Group 1 & 2
Total Thickness	1/8" (3.2 mm)	1/8" (3.2 mm)
Profile	Square and Sculptured	Square and Sculptured
Profile - Nose	80° angle	80° angle
Sizes	3' x 13" (.91 m x .33 m), 4' x 13" (1.22 m x .33 m), 5' x 13" (1.52 m x .33 m), 6' x 13" (1.83 m x .33 m)	3' x 13" (.91 m x .33 m), 4' x 13" (1.22 m x .33 m), 5' x 13" (1.52 m x .33 m), 6' x 13" (1.83 m x .33 m)  Abrasive Insert 2" (.50 mm)
Colors	36	36 Tread Colors, 10 Abrasive Tape Colors
Packaging	3' x 13" - 5 pcs, 28 lbs (12.70 kg) 4' x 13" - 5 pcs, 38 lbs (17.25 kg) 5' x 13" - 5 pcs, 47 lbs (21.32 kg) 6' x 13" - 5 pcs, 56 lbs (25.40 kg)	3' x 13" - 5 pcs, 28 lbs (12.70 kg) 4' x 13" - 5 pcs, 38 lbs (17.25 kg) 5' x 13" - 5 pcs, 47 lbs (21.32 kg) 6' x 13" - 5 pcs, 56 lbs (25.40 kg)
Adhesive	MR-911 Acrylic Adhesive Double Sided Tape	
Testing		
HUD/FHA	Passes	
Hardness (ASTM D2240)	Passes - Shore Type A ≥ 85	
Thickness (ASTM 386)	± 1/32" (0.8 mm)	
Static Load (ASTM F970)	Passes - Residual Indent ≤ 0.005"	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm2	
Smoke Density (ASTM E662)	Passes - < 450	
Slip Resistance (ASTM C1028, Dry)	Passes - ≥ 0.5 Leather; 0.6 Rubber	
Chemical Resistance (ASTM F925)	Passes	
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change	
Environmental Data		
Indoor Air Quality	FloorScore Certified; CDPH v1.1-2010	
Product Declarations	HPD	
LEED Scoreboard	May contribute to LEED credits: Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 -Low Emitting Materials	
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Certified	
Warranty		
	Limited 10-Year Commercial Warranty	
	Limited 10-Year Wear Warranty	
	Limited 5-Year Nose Warranty	

Color Anchor Stair Tread Collection

Style	ColorScape® Stair Tread	ColorScape® Stair Tread with Visually Impaired Strip
Construction	Thermoset Vulcanized Rubber - Type TS	Thermoset Vulcanized Rubber - Type TS
Classification	ASTM F2169 Class II, Group 1 & 2	ASTM F2169 Class II, Group 1 & 2
Total Thickness	1/8" (3.2 mm)	1/8" (3.2 mm)
Profile	Round, Square, and Sculptured	Round, Square, and Sculptured
Profile - Nose	80° angle	80° angle
Sizes	3' x 13" (.91 m x .33 m), 4' x 13" (1.22 m x .33 m), 5' x 13" (1.52 m x .33 m), 6' x 13" (1.83 m x .33 m)	3' x 13" (.91 m x .33 m), 4' x 13" (1.22 m x .33 m), 5' x 13" (1.52 m x .33 m), 6' x 13" (1.83 m x .33 m) Abrasive Insert 2" (.50 mm)
Colors	36	36 Tread Colors, 10 Abrasive Tape Colors
Packaging	3' x 13" - 5 pcs, 28 lbs (12.70 kg) 4' x 13" - 5 pcs, 38 lbs (17.25 kg) 5' x 13" - 5 pcs, 47 lbs (21.32 kg) 6' x 13" - 5 pcs, 56 lbs (25.40 kg)	3' x 13" - 5 pcs, 28 lbs (12.70 kg) 4' x 13" - 5 pcs, 38 lbs (17.25 kg) 5' x 13" - 5 pcs, 47 lbs (21.32 kg) 6' x 13" - 5 pcs, 56 lbs (25.40 kg)
Adhesive	MR-911 Acrylic Adhesive Double Sided Tape	
Testing		
HUD/FHA	Passes	
Hardness (ASTM D2240)	Passes - Shore Type A ≥ 85	
Thickness (ASTM 386)	± 1/32" (0.8 mm)	
Static Load (ASTM F970)	Passes - Residual Indent ≤ 0.005"	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm2	
Smoke Density (ASTM E662)	Passes - < 450	
Slip Resistance (ASTM C1028, Dry)	Passes - ≥ 0.5 Leather; 0.6 Rubber	
Chemical Resistance (ASTM F925)	Passes	
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change	
Environmental Data		
Indoor Air Quality	FloorScore Certified; CDPH v1.1-2010	
Product Declarations	HPD	
LEED Scoreboard	May contribute to LEED credits: Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 -Low Emitting Materials	
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Certified	
Warranty		
	Limited 10-Year Commercial Warranty Limited 10-Year Wear Warranty Limited 5-Year Nose Warranty	