

Style	ConnectStep® Stair Tread/Riser Combination	Risers/Stringer
Construction	Thermoset Vulcanized Rubber - Type TS	Thermoset Vulcanized Rubber - Type TS
Finish	Matte	Matte
Clasification	ASTM F2169 Class 2, Group 1 & 2, Grade 1	ASTM F2169 Class 1, Grade 1
Total Thickness	1/8" (3.2 mm)	1/8" (3.2 mm)
Profile	Round and Sculptured ColorScape® Sculptured ColorSpec®	Smooth
Profile - Nose	Square	N/A
Sizes	3' (.91m) - ColorScape® only 4' (1.22m) 5' (1.52m) 6' (1.83m)	3' (.91m) 4' (1.22m) 5' (1.52m) 6' (1.83m)
Height	9.5" – 13" step depths	7" coved riser/ 12"x36" length stringer
Colors	36	36
Packaging	5 pcs/carton (3' - 7lbs/pc - 35lbs; 4' - 9lbs/pc - 45lbs; 5' -11.5 lbs/pc - 57.5 lbs; 6' - 14 lbs/pc - 70 lbs)	20 pcs/carton (3' - 36 lbs; 4' - 50 lbs; 5' - 62 lbs; 6' - 74 lbs); (Stringers 12 x 26 - 64 lbs)
Adhesive	MR-911 Acrylic Adhesive Double-Sided tape MR-715 Epoxy caulk (optional) Used for the visually impaired with contrasting strip color	MR-101 Acrylic Adhesive MR-911 Acrylic Adhesive
Testing		
HUD/FHA	Passes	
ADAG (American Disability Act Guidelines)	Passes	
Hardness (ASTM D2240)	Passes - Shore Type A ≥ 85	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm²	
Smoke Density (ASTM E662)	Passes - < 450	
Slip Resistance (ASTM C1028, Dry)	Passes - ≥ 0.5 Leather; 0.6 Rubber	
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change	
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change	
Resistance to Mold/Mildew (ASTM G21/ ASTM E2180)	Passes - No More Than Slight Change	
Environmental Data		
Indoor Air Quality	FloorScore Certified, CDPH v11-2010	
Product Declaration	HPD	
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Certified	
Warranty		
	Limited 10-Year Commercial Warranty Limited 10-Year Wear Warranty Limited 5-Year Nose Warranty	