

Model 5942-69 — Recessed



Dual Roll Tissue Dispenser/Waste Receptacle

Product Materials

CABINET: 22 gauge stainless steel with exposed surfaces in architectural satin finish. Welded construction with burr-free edges.

FLANGE: 22 gauge stainless steel with exposed surfaces in architectural satin finish. One-piece seamless construction, 1" wide with ¼" return.

DOOR: 18 gauge stainless steel with full-length piano hinge and tumbler lock keyed like other Bradley units.

PUSH FLAP DOOR: 22 gauge stainless steel with exposed surfaces in architectural satin finish. Self-closing, with heavy-duty stainless steel

WASTE RECEPTACLE: leakproof molded plastic. 1.7 gal. capacity. **SPINDLES:** polyethylene, non-removable by user.

Capacity

Toilet Tissue Dispensers-Two standard core toilet tissue rolls through 51/4" in diameter. Box of 500 waxed paper liners are available by ordering part

Operation

Hinged access door permits servicing of components from one side. Door to be at 90 degrees for access to tissue spindle.

Installation

Verify all rough-in dimensions prior to installation. Requires rough wall opening 15%"W x 181/4"H x 41/4"D. Secure with mounting screws (included) at holes provided.

Guide Specification

Recessed combination unit shall include toilet tissue dispenser and napkin disposal, and be fabricated of stainless steel with seamless exposed surfaces in satin finish. Door and back panel shall be 18 gauge. Door shall have piano hinge and tumbler lock.

Overall dimensions: 171/8"W x 20"H x 41/2"D.

选 ADA Compliant



Consult local and national accessibility codes for proper installation guidelines.




Conformity and compliance to local and national codes is the responsibility of the installer.



© 2024 Bradley P.O. Box 309. Menomonee Falls. WI 53052-0309 800 BRADLEY (800 272 3539) +1 262 251 6000 bradleycorp.com





Rough wall opening: 15%" (391)W x 1814" (464)H x 414" (108)D

Dim. "A" Key Surface:	For Dim. "A"	Top of Rough Wall Opening	Bottom of Rough Wall Opening	For Bottom Toilet Paper Opening Lower Lip @ Dim. "A"
Top of 1½" grab bar to finished floor (installed with 1½" clearance)	Not Applicable	37" (940)	18¾" (476)	19" (483)
	36" (914)	33" (838)	14¾" (375)	15" (381)

Grab bars must be ordered separately. To learn more about Bradley's wide variety of grab bar configurations, visit bradleycorp.com.