



A WATTS Brand

7906A, 7906AVB

Recessed Hose Box w/ Hot & Cold Supplies

- Hot & Cold Supplies
- Sturdy Stainless Steel
- Non-Protruding
- For Non-Freezing Environment

Specifications

Material

Box and wall flange or flange/door assembly are fabricated of 18 gauge type 300 series stainless steel. All exposed stainless steel surfaces are polished to a #4 satin finish. Stop and valve bodies are cast brass. Exposed valve parts are chrome plated.

Construction

All seams are heliarc welded and ground smooth.

Material

Supply inlets are 1/2" nom. brass female. Outlets are 3/4" male hose threads.

Wall Anchoring

Box is furnished with four stainless steel mounting tabs which provide a secure means for anchoring to the wall.

Construction

Recessed hose box with hot and cold screwdriver stops and valves, wall flange or flange/door assembly, and 3/4" hose connections (2" nominal/2-3/8" OD stainless steel drain outlet). Flange/door assembly comes standard with cylinder lock.

Models (Must select one)

Model	Description
7906A (less door)	Recessed Hose Box w/Cold Supply (S91-065)
7906A (with door)	Recessed Hose Box w/Cold Supply (S91-063)
7906AVB (less door)	Recessed Hose Box w/Cold Supply and Vacuum Breaker (S91-066)
7906AVB (with door)	Recessed Hose Box w/Cold Supply and Vacuum Breaker (S91-064)

