

Model 6562 – Liquid Soap **Brade**x® Model 6562-73 – Foam Soap **Brade**x®

Tank Type Vertical

Surface-Mounted

ADA Compliant

Product Materials

Body: 20 gauge stainless steel with exposed surfaces in architectural satin finish.

Back: 20 gauge stainless steel; heliarc welded to the body.

Wall Plate: stainless steel.

Liquid Soap Dispenser: chrome-plated brass housing with ABS plastic

mechanism.

Foam Soap Dispenser: chrome-plated ABS mechanism.

Capacity

40-oz. liquid or bulk foam soap.

Operation

Push-in valve dispenses measured amount of vegetable or coconut oil liquid soaps, synthetic detergents, antiseptic solutions or foam soap with less than 5 lbs. of force. Sight gauge indicates refill time. Locked filler top opens with special key provided.

Bradley foam soap valves work with majority of bulk foam soap.

Installation

Verify all rough-in dimensions prior to installation. Secure separate mounting bracket to wall. Slide dispenser into place and secure locking screw through filler hole.

Guide Specification

Surface-mounted soap dispenser shall be fabricated of 20 gauge satin finish stainless steel. Dispenser shall have completely concealed mounting, vandal-resistant filler hole cover and sight gauge. Push-in corrosion-resistant soap valve. Capacity: 40-oz. liqiod or bulk foam soap. Requires less than 5 lbs. of force to dispense soap.

Overall dimensions: 4-13/16"W x 8-1/4"H x 2-7/8"D.

Service Kits

Liquid Soap Valve - P15-408 Foam Soap Valve - P15-510

Orders composed of products indicated as **Bradex**® will be available to ship in three days after receipt of order at the factory. There is no pricing penalty for this service from Bradley.


Page 1 of 2 1/31/2024 This information is subject to change without notice. Bradley_SoapDispenser_6562



& ADA Compliant

- Consult local and national accessibility codes for proper installation guidelines.
- Conformity and compliance to local and national codes is the responsibility of the installer.





Dim. "A" Key Surface:	For Dim. "A"	Top of Unit	Bottom of Unit
Push button top to finished floor	40" (1016mm)	46¾" (1187mm)	38½" (978mm)
	38" (965mm)	44¾" (1137mm)	36½" (927mm)
	36" (914mm)	42¾" (1086mm)	34½" (876mm)
	34" (864mm)	40¾" (1035mm)	32½" (826mm)
Rough wall opening:			
Surface Mount:	No rough wall opening, see overall dimensions		

Orders composed of products indicated as **Bradex®** will be available to ship in three days after receipt of order at the factory. There is no pricing penalty for this service from Bradley.

Page 2 of 2 1/31/2024 This information is subject to change without notice. Bradley_SoapDispenser_6562