



A WATTS Brand

Euro Style Urinal Screens

Glass – SKYLINE Series

SKYLINE Series Features

- Elegant option in enameled tempered glass
- Modern minimalist design
- Optimal for high end application
- Creates light, airy space
- Scratch resistant and easy to clean
- Strong, long-lasting, and safe
- Available in a range of standard colors
- 100% recyclable

Construction

Scratch-proof, tempered glass with ceramic screen printing is 0.4" (10mm) and fitted to stainless steel connecting brackets and fittings. All corners are polished smooth for aesthetic and safety purposes. Materials are resistant to stains and corrosion. Panel sizes can be customized when wider than 15.7" (400mm). For accuracy, measurements should be taken to the closest millimeter. See data table for support and stabilization guide.

Sight Screens

Panels that are 27.6" (701mm) or larger are attached to the wall with 6 stirrup brackets, proportionately spaced, and a floor to ceiling post at front of panel. Posts are drilled into the floor and ceiling approximately 1.57" (40mm). Cover plates are provided to conceal screws.

Urinal Screens

Panels that are 15.8" – 27.5" (401mm – 700mm) may be wall hung with 6 stirrup brackets, or wall hung with stirrup brackets and foot braced, dependant on width of panel and stabilization necessary.

Brackets

Stainless steel stirrup-type brackets are provided for all sizes as shown and proportionately spaced. All bracket holes are pre drilled.

Feet

Feet are constructed of stainless steel and match feet on the partitions.

Hardware

Screens shall be provided with all hardware and fastenings for a complete installation.

Product Compliance

Listed by UL Environment to


- GreenGuard Gold



Verify all rough-in dimensions prior to installation.
Consult local and national codes. Conformity and compliance to local and national codes is the responsibility of the installer.

Euro Style Urinal Screen with Stirrup Bracket & Floor to Ceiling Post


For panels that are 27.6" (701mm) or wider.



Note: Location of bracket drill holes is dependent on height of panel.

Wall-Hung and Foot Braced Euro Style Urinal Screen

For panels between 15.8" (401mm) and 27.5" (700mm) wide.



Note: Location of bracket drill holes is dependent on height of panel.

Wall-Hung Urinal Screen with Stirrup Brackets

For panels 15.7" (400mm) wide.



Note: Location of bracket drill holes is dependent on height of panel.



A WATTS Brand

Euro Style Urinal Screens

Glass – SKYLINE Series

Panel Width	<15.7" (400mm)	15.8" (401mm) - 27.5" (700mm)	>27.6" (701mm)
Application	Urinal Screen	Urinal Screen	Sight Screen
Type of Bracket	Stirrup	Stirrup	Stirrup
Number of Brackets	4	6	12 Total, 6 at post, 6 at wall
40mm (1.57") Support Post	No	No	Yes
Foot Brace	No	Yes	No
Max Screen Height	35.4" (900mm)	85.1" (2162mm)	98.4" (2500mm)
Max Support Post Height	N/A	N/A	118.1" (3000mm)
AFF ¹	Variable	1.97" (50mm)	1.97" (50mm)

¹ AFF cannot be changed on panels 15.8" (401mm) or wider. Standard U.S. urinal screens are 24" (610mm) wide x 63" (1600) high, wall hung with 6 stirrup brackets and foot braced.

Standard Selections (select one)

Colors

NOTE: Click on any swatch to view as a larger image.

7038 - Agate Gray ☐ Agate Gray

9003 - Alabaster ☐ Alabaster

7012 - Basalt Gray ☐ Basalt Gray

5014 - Coastal Blue ☐ Coastal Blue

7035 - Morning Fog ☐ Morning Fog

9017 - Obsidian ☐ Obsidian

1013 - Oyster White ☐ Oyster White

6019 - Seagrass ☐ Seagrass

6034 - Tide Pool ☐ Tide Pool

Custom Custom color: _____

Hardware

Stainless Steel (STD)

Verify all rough-in dimensions prior to installation.
Consult local and national codes. Conformity and compliance
to local and national codes is the responsibility of the installer.

Page 2 of 2

6/12/2024

[View Latest Version](#)

This information is subject to change without notice.

Bradley_UrinalScreens_SKYLINE

© 2024 Bradley
P.O. Box 309, Menomonee Falls, WI 53052-0309
800 BRADLEY (800 272 3539) +1 262 251 6000
bradleycorp.com