



A WATTS Brand

Euro Style Restroom Partitions Cleaning & Maintenance

Glass — LUCENT Series & SKYLINE Series

Material Description

The enameled tempered glass with ceramic screen printing is 0.4 inches (10 mm) thick and is completely scratch-resistant, which is achieved by using vitreous enamel paints. The glass stands up well to graffiti - any marks from pens, felt tips or spray paint are easily removed.

Cleaning Guidelines

After Installation

- Do not use any aggressive acidic or alkaline cleaners to clean the surface after installation. These harsh cleaners can attack the material surface and cause damage.
- Only use cleaners that are free of halogens (for example, chlorides), meaning the cleaner does not consist of hydrochloric acid or any other acid such as muriatic acid (commonly used in tile cleaner). Cleaners containing acid will attack aluminum and stainless steel parts, causing corrosion to develop over time.
- To maintain a shiny surface, use a soft clean cloth or sponge when cleaning. Do not use abrasive cleaners (brush, scrub pad, etc.) or sharp/metal items like steel wool on the surface when cleaning.
- For regular cleaning, use ordinary household cleaner on the latches and hardware.

Swimming Pool Environments

- Because of the condensation that contains chloride, cleaning the stainless steel surfaces every day is recommended.
- Best practice is to use plain, clean water for cleaning. If surfaces are not cleaned daily, the clarity of the surface will degrade and corrosion will develop over time.

Stubborn Stains

- To remove stubborn stains like grease and graffiti, use isopropyl or spirit alcohol. On occasion, a slightly alkaline cleaner can be used, however, verify the cleaner is not acidic to prevent surface attacks.

Maintenance Guidelines

- All moveable parts are maintenance-free and do not have to be greased.
- Steam-blasting is not advised as the high-pressure water jet can cause the glue to release.