## L'ANTIC COLONIAL

Model: HERITAGE VALENCIA

Codes: 100336807 Group: G-226

Format: 7 7/8"X7 7/8"X43/128" approx.



	RECOMMENDATIONS
Recommended adhesive	100201543 ONE-FLEX PREMIUM GRIS 25KG
Recommended joint	100236834 COLORSTUK RAPID GRIS N 5KG
Recommended joint (wet area)	100236834 COLORSTUK RAPID GRIS N 5KG
Recommended adhesive (wet area)	100201543 ONE-FLEX PREMIUM GRIS 25KG

	DIMENSION	AL FEATURES
Length and width deviation	±0.5%	UNE-EN ISO 10545-2*
Side straightness deviation	±0.5 %	UNE-EN ISO 10545-2*
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*
Surface flatness deviation	±0.5 %	UNE-EN ISO 10545-2*

## FEATURES



Gloss-free



 $\label{eq:material} \text{Material suitable for use on outdoor walls.}$ 



Material suitable for use on indoor floors.



Material recommended for installation on the floor.



Material suitable for use on indoor walls.



There are slight color changes between pieces.

	PHYSICAL PROPERTIES	
Water absorption	Bla	ISO 10545-3*
Breaking strength	>472.29 LBF	>292LBF*
Resistance to thermal shock	PASS	ISO 10545-9*
Crack resistance	PASS	ISO 10545-11*
Flammability	A1f I/A1	EN 13501-1*
Flexural strength	>51 MPA	ISO 10545-4*
Slip resistance (pendulum-wet)	CL 1 (28)	EN 16165 Anexo C*
Slip resistance (ramp)	R9	EN 16165 Anexo B*
Slip resistance (pendulum-dry)	80	
Dynamic coefficient of friction	0.72	
Abrasion resistance	PEI 3	





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use cleaning agents containing hydrofluoric acid. In public places the tiles must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

HERITAGE VALENCIA

## L'ANTIC COLONIAL

	CHEMICAL PRO	PERTIES
Stain resistance	CL 5	ISO 10545-14*
Resistance to chemicals	GA/GLA/GHA	ISO 10545-13*

	PACKING	
Sales units per box	9.47 SQF/CS	
Sales units per pallet	568.33 SQF/PAL	
Sales units per unit	0.43 SQF/ST	
Sale unit	M2	
Base unit	ST	
Net weight	470.45 LB/SQF	
Gross weight	481.13 LB/SQF	





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use cleaning agents containing hydrofluoric acid. In public places the tiles must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.