L'ANTIC COLONIAL

Model: AC4 ENDLESS 1L BROOKLYN

Codes: 100199491 Group: G-210

Format: 9 155/256"X49 165/256"X81/256" approx.



| COMPOSITION | | | | | | |
|-------------|---------|------|------------------|--|--|--|
| | | Size | Material | Type of material | | |
| | Layer 1 | 0.2 | Melamine | Aminoplastic thermosetting resins | | |
| | Layer 2 | 0.2 | Decorative paper | | | |
| | Layer 3 | 7.5 | HDF | High-density Fiber Board and water-repellent glues | | |
| | Layer 4 | 0.1 | Backside | Sheets of kraft paper impregnated with phenolic resins | | |

CERTIFICATIONS CARB: Phase II compliant

FEATURES



Carb certification

Boards that have continuity between them, thus achieving the optical effect of



Imitates the surface of wood



Beveled cut on the long sides of the board in order to create a continuity effect



Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.



20 year warranty for domestic use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.



5 year warranty for commercial use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.



Format where only one board has been used to finish the entire base surface



Is suitable for installing on water radiant heating



PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests



Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.



23. Intensive residential



32. General commercial







ACA ENDLESS 11 BROOKLYN

L'ANTIC COLONIAL

| DIMENSIONAL FEATURES | | | | | | |
|--|--|--------------|--|--|--|--|
| Item thickness | ≤0.50 mm | EN 13329* | | | | |
| Length of face | ≤0.50 mm | EN 13329* | | | | |
| Width of face | ≤0.20 mm | EN 13329* | | | | |
| Squareness of the item (q) | ≤0.20 mm | EN 13329* | | | | |
| Straightness of face | ≤0.30 mm/m | EN 13329* | | | | |
| Flatness of item (f) | fw,Cóncavo≤0.50% fw,Convexo≤1%/fl,Cóncavo≤0.15% fl,Convexo≤0.20% | EN 13329* | | | | |
| Joint between items | ≤0.20 mm | EN 13329* | | | | |
| Difference in height among items | ≤0.15 mm | EN 13329* | | | | |
| Dimensional variations related to changes in relative moisture | ≤0.90 mm | EN 13329* | | | | |
| Uv light fastness | ≥4 | EN 438-2,16* | | | | |

| LABORATORY TESTS | | | | | | |
|--------------------------------|-----------------------------------|--------------------|--|--|--|--|
| Resistance to abrasion | AC4 | UNE EN 13329:2000* | | | | |
| Impact resistance | IC2 | EN 13329* | | | | |
| Resistance to staining | Grado 5 (G 1 y 2) y Grado 4 (G 3) | EN 438* | | | | |
| Resistance to cigarette burns | 4 | EN 438* | | | | |
| Furniture leg effect | No damage | EN 424* | | | | |
| Castor chair effect | No damage | EN 425* | | | | |
| Swelling in thickness | ≤18% | UNE-EN 13329:2000* | | | | |
| Dimensional stability | 0.03% | EN 434:1994* | | | | |
| Formaldehyde emissions | E1 | EN 717* | | | | |
| Slip resistance (pendulum-wet) | CL 1 (33) | EN 16165 Anexo C* | | | | |
| Tensile strength of joints | F≥1 kN/ml | EN 13329* | | | | |
| Fire resistance | Cfl-s1 | EN 13501* | | | | |
| Heat resistance | R=0.057 m2 K/W | ISO 8302* | | | | |
| Curvature | 0.06 mm | | | | | |
| Swelling in thickness | ≤18% | ASTM D 1037* | | | | |
| Slip resistance (dcof) | 0.58 | ANSI A137.1* | | | | |
| Critical radiant flux | Cfl | EN ISO 9239-1* | | | | |
| Smoke density (burning) | s1 | EN 13501-1* | | | | |
| Density of the board | 925 ±5 KG/M3 | UNE EN 323* | | | | |
| Slip resistance (pendulum-dry) | 52 | EN 16165 Anexo C* | | | | |

| PACKING | | | | | | |
|------------------------------|----------------|--|--|--|--|--|
| Sales units per box | 26.5 SQF/CS | | | | | |
| Sales units per pallet | 794.85 SQF/PAL | | | | | |
| Sales units per unit | 3.31 SQF/ST | | | | | |
| Sale unit | M2 | | | | | |
| Base unit | ST | | | | | |
| Sales units per square meter | 1 M2 | | | | | |
| Net weight | 184.56 LB/SQF | | | | | |
| Gross weight | 191.66 LB/SQF | | | | | |

| SPECIAL PIECES | | | | | | | | | |
|----------------|--|-------|---------------|-----------------|----------------|-----|------------|----------------|----------------|
| SAP | Description | Group | Boxes | Pallet | Units | SKU | Basic Unit | Net Weight | Gross weight |
| 100153849 | IGUALACION ENDLESS 1L BROOKLYN 4X270X1 | G-155 | 20 PIECES/BOX | 1000 PIECES/PAL | 9.26 PIECES/M2 | - | - | 0.77 KG/PIECES | 0.8 KG/PIECES |
| 100176679 | MAMPERLAN AC4 ENDLESS 1L BROOKLYN7X120X3 | G-163 | 2 PIECES/BOX | 200 PIECES/PAL | 11.9 PIECES/M2 | - | - | 1.58 KG/PIECES | 1.64 KG/PIECES |
| 100153886 | TRANSICION ENDLESS 1L BROOKLYN 4X270X1 | G-155 | 20 PIECES/BOX | 1000 PIECES/PAL | 9.26 PIECES/M2 | - | - | 0.77 KG/PIECES | 0.77 KG/PIECES |
| 100153893 | ZOCALO ENDLESS 1L BROOKLYN 8X220X1,5 | G-107 | 14 PIECES/BOX | 560 PIECES/PAL | 5.68 PIECES/M2 | - | - | 1.8 KG/PIECES | 1.86 KG/PIECES |





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places, this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

06/02/2025