CIRRUS® Profiles Chamfered, Beveled & Classic

Chamfered, Beveled & Classic Step™ Tegular medium texture







CAD/Revit® drawings at: armstrongceilings.com/cadrevit

Cirrus Profiles - Classic Step panels with Suprafine XL 9/16" suspension system

Medium texture panels, with a variety of dimensional edge details; offer both Sustain® and Total Acoustics® panel performance.

KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels:
 NRC + CAC = Total Acoustics performance
- Cirrus® panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Classic edge details on refined Cirrus texture
- · High quality factory-finished edge detail
- Ideal combination of sound absorption and blocking
- Mold- and mildew-resistant surface
- · USDA-Certified Biobased Product 91%
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

COLOR



White (WH)

DETAILS (Other Suspension Systems compatible. Refer to listing on next page.)









- 1. Cirrus® Chamfered
- 2. Cirrus® Classic Step
- 3. Cirrus® Beveled Tegular
- 4. Cirrus® Classic Step with Suprafine® 9/16" suspension system



Chamfered, Beveled & Classic Step™ Tegular medium texture

USDA CERTIFIED BIOBASED PRODUCT

SUSTAIN High Performance Sustainable Ceiling Systems Declare.

Calculate sustainability with Ecomedes armstrongceilings.com/ecomedes CONTENT

VISUAL SELECTION

PERFORMANCE SELECTION Dots represent high level of performance.

\$\$\$\$

| armstrongceilings. com/suspdwgs | Susp. Dwg. | Item No. | Dimensions (Inches) | | UL Clar Acou | ssified stics | Total | Fire Performance | Light Reflect | Anti-Mold/ Blog-oig-oig-oig-oig-oig-oig-oig-oig-oig-o | Sag Resistant Resistant | Certified Low VOC Emissions | Durability | Recycled Content | Recycle Program | 30-Yr Warranty |
|---|---------------|----------|------------------------|---|-----------------|------------------|----------------|------------------|---------------|---|-------------------------------|--------------------------------|------------|---------------------|--------------------|----------------|
| CIRRUS® Profiles – Chamfered* 15/16" Tegular | 17 | 628 | 24 × 24 × 3/4" | | 0.65 | 35 | GOOD (iii)) | Class A | 0.85 | 0 | ٠ | 0 | Std | ٠ | ٠ | • |
| 9/16" Tegular | 30 | 557 | 24 × 24 × 3/4" | | 0.65 | 35 | GOOD | Class A | 0.85 | 0 | • | 0 | Std | • | • | • |
| CIRRUS® Profiles – Beveled 9/16" Tegular | 29 | 590 | 24 × 24 × 3/4" | Ħ | 0.65 | 35 | GOOD | Class A | 0.85 | 0 | Std | ٠ | Std | ٠ | ٠ | 10-Yr |
| CIRRUS® Profiles – Classic Step™ 15/16" Tegular | 19 | 626 | 24 × 24 × 3/4" | Ħ | 0.65 | 35 | GOOD | Class A | 0.85 | ٠ | Std | ٠ | Std | ٠ | ٠ | 10-Yr |
| | 18 | 591 | 24 × 24 × 3/4" | | 0.65 | 35 | GOOD | Class A | 0.85 | • | ٠ | • | Std | ٠ | ٠ | • |
| 9/16" Tegular | 31 | 591 | 24 × 24 × 3/4" | | 0.65 | 35 | GOOD | Class A | 0.85 | 0 | 0 | ۰ | Std | • | • | • |
| | 32 | 585 | 24 × 24 × 3/4" | Ħ | 0.65 | 35 | GOOD | Class A | 0.85 | 0 | Std | ۰ | Std | • | • | 10-Yr |

Total Acoustics* ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
 GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)
 * Ceiling design copyrighted by AWI Licensing LLC.

SUSPENSION SYSTEMS

Chamfered

15/16" Prelude®

Prelude Classic Step 9/16" Suprafine Chamfered Suprafine Beveled

Suprafine Classic Step

PHYSICAL DATA

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

ASTM E1264 Classification

Type A, Form A1.2, Pattern F, I; Fire Class A

Humidity/Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications. Excludes items 585, 590, 626.

Anti-Mold/Mildew

Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard", Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

High Recycled Content

Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value

R Factor – 1.9 (BTU units) R Factor – 0.33 (Watts units)

30-Year Performance Guarantee & Warranty When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton 590, 591 - 1.06 LBS/SF; 48 SF/CTN

557, 585, 626, 628 - 1.17 LBS/SF; 48 SF/CTN Minimum Order Quantity

1 carton

Metric Items Available 628M, 557M, 590M, 591M, 626M, and 585M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details



MINERAL FIBER – Standarc