



FeltWorks™ Acoustical Panels Armstrong World Industries

Final Assembly: Gyeonggi-do, South Korea

Life Expectancy: 10+ Year(s)

End of Life Options: Salvageable/Reusable in its Entirety,
Recyclable (100%)

Ingredients:

Polyethylene Terephthalate; Flame Retardant; Undisclosed (0.3-0.6%)¹; Benzoxazole, 2,2'-(1,2-ethenediyl-di-4,1-phenylene)bis-; White Tint; Black Tint; Blue Tint; Iron Oxide; Yellow Tint

¹LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|------------------------------|
| <input type="checkbox"/> LBC Red List Free | % Disclosed: 99.4% at 100ppm |
| <input checked="" type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

ARM-0048

EXP. 01 JAN 2026

Original Issue Date: 2019

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY

INTERNATIONAL LIVING FUTURE INSTITUTE™ living-future.org/declare