

LEDGES®

Tegular
smooth texture



Ledges® I panels with Prelude® XL 15/16" suspension system



Ledges® II panels with Suprafine® XL 9/16" suspension system

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit

The dimensional look of old-world plaster ceilings in two classic designs.

KEY SELECTION ATTRIBUTES

- Dimensional, sculptured visual
- Affordable and practical alternative to embossed plaster panels
- Non-directional visual reduces installation time and scrap
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

NOTE: Not recommended for areas requiring acoustical performance

COLOR



White
(WH)

FACE VIEWS



Ledges® I panel



Ledges® II panel

DETAILS



1. Ledges® I Flush Tegular
2. Ledges® II Flush Tegular
3. Ledges® I with Prelude® 15/16" suspension system
4. Ledges® II with Suprafine® 9/16" suspension system

LEDGES®

Tegular
smooth texture

Declare.

LEED® WELL | LBC

UP TO 43% RECYCLED CONTENT

Calculate sustainability with Ecomedes
armstrongceilings.com/ecomedes

energy management
construction waste mgmt
regional materials
design for flexibility
EPD
recyclable/ biobased producer resp.
biobased materials
recycled content
sourcing of raw materials
material ingredient reporting
low emitting/ materials
lighting quality
acoustics

LOCATION DEPENDENT

VISUAL SELECTION

PERFORMANCE SELECTION Dots represent high level of performance.

\$\$\$\$

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
LEDGES® I 15/16" Flush Tegular	3	8011	24 × 24 × 3/4"
LEDGES® II 9/16" Flush Tegular	25	8013	24 × 24 × 3/4"

UL Classified Acoustics	Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold/ Mildew	Sag Resistant	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	Warranty
NRC + CAC =										
N/A 35 *	N/A	Class A	0.80	N/A	Std	N/A	Std	Std	*	1-Yr

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Wet-formed mineral fiberSurface Finish
Factory-applied latex paintFire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL* labeled).ASTM E1264 Classification
Type A, Form A1.2, Pattern G; Fire Class A

Humidity/Sag Resistance

Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Insulation Value

R Factor - 1.6 (BTU units)
R Factor - 0.28 (Watts units)1-Year Limited Warranty
Details at armstrongceilings.com/warrantyWeight: Square Feet/Carton
8011 - 0.90 LBS/SF; 48 SF/CTN
8013 - 0.90 LBS/SF; 32 SF/CTNMinimum Order Quantity
1 carton