




## Lyra™ PB High CAC Ceiling Panels Armstrong World Industries

**Final Assembly:** Hilliard, Ohio, USA  
**Life Expectancy:** 30 Year(s)  
**Embodied Carbon:** 0.681 kg CO2eq   
**Declared Unit:** 1ft2  
**End of Life Options:** Take Back Program (Armstrong Ceiling Recycling Program), Recyclable (100%)

### Ingredients:

Glass, oxide, chemicals; Mineral Wool; Clay; Perlite; Quartz; Starch, polymer with 2-propenoic acid, graft, sodium salt; Cellulose; Corn Starch; Fats and Glyceridic oils, vegetable, polymd., oxidized; Calcium Carbonate; Titanium dioxide; Aluminum hydroxide; Polyvinyl acetate; Siloxane; Propanol; Polyvinyl alcohol; Acrylic Acid; Aluminum Trihydrate; Water; Copolymer of acrylic acid and alkyl vinyl ester; Calcium carbonate; Proprietary Ingredient (< 0.1%)<sup>1</sup>; Mica; Silica; Diatomaceous Earth

<sup>1</sup>LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

### Living Building Challenge Criteria: Compliant

#### I-13 Red List:

- |   |                              |
|---|------------------------------|
| <input type="checkbox"/> LBC Red List Free                | % Disclosed: 99.9% at 100ppm |
| <input checked="" type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable  |
| <input type="checkbox"/> Declared                         |                              |

**I-10 Interior Performance:** CDPH Standard Method v1.2-2017

**I-14 Responsible Sourcing:** Not Applicable

ARM-0018  
EXP. 01 AUG 2025  
Original Issue Date: 2016