



Product Specifications

|                     |                                      |
|---------------------|--------------------------------------|
| Construction        | Cut Pile                             |
| Backing             | Standard Back                        |
| Dye Method          | Solution Dyed                        |
| Fiber Type          | Solution Dyed PET                    |
| Face Weight         | 32 oz./sy (1085 grams/m2)            |
| Pattern Repeat      | N/A                                  |
| Gauge               | 1/10 (3.94 rows/cm)                  |
| Standard Width      | 12 ft 3.66 m                         |
| Standard Adhesive   | Commercialon Premium Carpet Adhesive |
| Standard Warranties | Living Spaces<br>Standard Back       |

Special Technologies

|                      |          |
|----------------------|----------|
| ProTex® Soil Release | Standard |
|----------------------|----------|

Environmental Specifications & Tests

|                        |                                    |
|------------------------|------------------------------------|
| NSF 140:               | Gold Certified                     |
| Total Recycled Content | 0%                                 |
| Radiant Panel          | Class 1                            |
| Smoke Density          | Less than 450 flaming (ASTM E 662) |
| Static Test            | Less than 3 kv (AATCC-134)         |
| ADA Compliance         | Compliant For Accessible Routes    |
| Pill Test              | Yes                                |
| Lightfastness          | Yes                                |

Colorways




HIL15 Soft Beige




HIL25 Earth



HIL51 Cool Grey



HIL53 Morning Mist



HIL58 Rock



HIL75 Gentle Taupe