



Product Specifications

Construction	Patterned Scroll
Backing	PremierBac® Plus
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	24 oz./sy (814 grams/m2)
Pile Density	9191 oz./y3 (340.81 kg/m3)
Pattern Repeat	24.00" (w) x 32.50" (l) approx. (60.96cm x 82.55cm)
Gauge	1/12 (4.72 rows/cm)
Stitches Per Inch	11.06 stitches/in (4.35 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Commercialon Premium Broadloom Adhesive PremierBac Plus Encore SD Ultima Fiber
Optional Warranties	Endure Plus TitanBac Plus Encore® 100 Fiber






Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	50%
Radiant Panel	Class 1
Smoke Density	Less then 450 flaming (ASTM E 662)
Static Test	Less then 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways

					
SPW12 Linen Reed	SPW13 Khaki Weft	SPW38 Alpine Loo...	SPW44 Blue Tread...	SPW49 Midnight B...	SPW53 Silver Warp
					
SPW55 Grey Bobbin	SPW58 Black Selv...	SPW76 Wildwood ...	SPW77 Graphite He...	SPW98 Currant Shu...	