



Product Specifications

Construction	Cut Pile
Backing	PremierBac® Plus (A)
Dye Method	Beck Dyed
Fiber Type	Type 6,6 Nylon
Face Weight	36 oz./sy (1221 grams/m2)
Pile Density	6113 oz./y3 (226.67 kg/m3)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Stitches Per Inch	11.33 stitches/in (4.46 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Encore RE & Type 6,6 Nylon Fiber
Optional Warranties	Endure Plus TitanBac Plus






Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	49.5%
Radiant Panel	Class 1
Smoke Density	Less then 450 flaming (ASTM E 662)
Static Test	Less then 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways

					
PC610 Blissful Be...	PC611 Es Tu Ecru	PC612 Almond Ro...	PC614 Irish Cream	PC621 Cabana Ba...	PC622 Citrine Che...
					
PC624 Gold Metal	PC625 Queen Bee	PC631 Lamplight	PC632 Silver Leaf	PC633 Frog Prince	PC634 Olive Sprig
					
PC635 Tarragon	PC636 Green Horn...	PC638 Jolly Green G...	PC639 On The Roc...	PC642 Morning GL...	PC643 Alpine
					
PC644 Ship To Sho...	PC645 Unreal Teal	PC647 Still Waters	PC649 My Blue Cr...	PC651 Hubcap	PC654 Steel Away
					
PC656 Outer Space	PC659 Infinity & Be...	PC672 Basket Case	PC673 Hat Box Br...	PC674 Mr. Potato H...	PC677 Paw Print
					
PC679 Chocolate ...	PC684 Rust Away	PC685 See Rock C...	PC688 Always Ruby	PC696 Three Wish...	PC699 Perky Purple