



Installation Methods: Brick, Monolithic, Ashlar, Quarter Turn

Product Specifications




Construction	Textured Loop
Backing	Nexus® Modular
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	22 oz./sy (746 grams/m2)
Pile Density	9290 oz./y3 (344.48 kg/m3)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Standard Size	24" x 24" approx. (60.96cm x 60.96cm)
Standard Adhesive	Commercialon Premium Modular and LVT Adhesive
Optional Adhesive	TileTabs
Standard Warranties	Nexus Modular Commercialon Adhesive for Modular Carpet & LVT Nexus FC Cushion Encore SD Ultima Fiber
Optional Warranties	Commercialon High Moisture Adhesive for Modular Carpet and LVT Advance Modular Backing Nexus Cushion Modular Adhesive Advance Modular Adhesive Tile Tabs Encore® 100 Fiber

Special Technologies

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	44.8%
Radiant Panel	Class 1
Smoke Density	Less then 450 flaming (ASTM E 662)
Static Test	Less then 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways

 WTC11 Bone White	 WTC15 Gamboge	 WTC33 Sap Green	 WTC35 Celadon	 WTC37 Turquoise	 WTC38 Phthalo Gr...
 WTC44 Cerulean	 WTC46 Lapiz	 WTC47 Ultramarine	 WTC49 Dark Cobalt	 WTC51 Smoke	 WTC54 Payne's Gr...
 WTC56 Lead Gray	 WTC59 Soot Black	 WTC68 Rose Madd...	 WTC76 Raw Sienna	 WTC78 Umber	 WTC86 Vermillion
 WTC88 Scarlet Red	 WTC98 Mars Violet				